

IPCDS-RWB

Double Sided IP Clock with Wall Mount and Flashers

Capabilities

Clock:

- 3" numbers/text
- Atomic time
- Never needs setting
- Auto-adjust for Daylight Savings
- Display 4 or 6 digits
- Configurable fonts and colors

Audio:

- Two 4" High efficiency PA Speakers:
- Bell scheduling, alerts, reminders, clock chimes, and alarms via Clockwise or 3rd party software
- Voice paging from a PC or IP phone, scheduled or ad hoc.
- Use provided notifications, alarms, audio files (sport, holiday, traditional, etc.), or your own

Flashers:

- Configurable for emergencies or alerts
- · Individually controllable
- · One red, one white, one blue



Two way talking/Intercom

Paging Supervision

Hands-free talk back

Monitoring

Scrolling Text:

Send many types of messages:

- Custom Configuration
- Reminders
- Alerts
- Advertising
- RSS/Twitter/News/Weather/Stock feeds
- Configurable fonts and colors
- 1 or 2 Line Display

Automatically dim for different times of day. Reduce power usage at night to save energy

Timer/Stopwatch:

- Display 4 or 6 digits
- · Configurable fonts and colors
- Count up or down
- Count days, hours, minutes, seconds, 1/100ths of seconds
- Display timer and clock simultaneously

Features

Built in Web Server:

- Send text messages to it from the web page
- · Configurable brightness and volume
- Configurable fonts
- Configurable NTP time server, time zone, etc.
- Device Status
- Field upgradable

Line In/ Out:

- Independent line-in.
- Can be configured to send line in audio to the speaker and/or add additional speakers

Easy Installation:

- Only requires CAT 5 connection (up to 300ft) to network
- Power over Ethernet (no power cord or adapter). No other equipment needed

GPIO:

- 2 inputs, 1 output
- Activate via telephone or programmatically

Multicast:

 Full multicast and broadcast support.
Send audio and/or scrolling text to individual, multiple, or all devices simultaneously.

Stop Watch / Timer:

 Count up and down days, hours, minutes, seconds, 1/100ths, with configurable sounds and colors. Eventbased trigger.

Sound Masking:

• Generate configurable pink noise via push button or programmatically for sound masking

Two Way Communication:

- Activate via push button
- Allows for full duplex hands free communication

Options

Optional button for hand-free push to talk

IP Clock Overview

The IP Clock is a Power over Ethernet (PoE, PoE+) synchronized clock and intercom that requires only an RJ-45 connector to connect to existing data networks. Simultaneously, broadcast to both phones and speakers. The clock auto synchronizes and can be used as a scrolling text display for all sorts of streaming messages. Built in microphone and speaker for two way communications.



Supported Protocols

- SIP
- DHCP
- IPv4
- IGMP
- HTTP
- ICMP
- SLP
- TCP/IP
- TFTP
- UDP
- NTP
- MDNS and MDNS-SD
- SNMPV1 & SNMPV2c

Specifications

- Weight: 22 lbs
- Approx. 23"x 5.5"x 6.5"
- PoE (IEEE802.3af) 15.4 W
- PoE+ (IEEE802.3at) 30.0 W
- 10/100 Mb network connection
- PoE+ recommended

Speaker Size:	4"
Average Sensitivity:	96dB, 1W/1M
AudioPower:	8 W / 16 W
Frequency Response:	150 Hz - 17 kHz
Polar Plot:	See diagram 1




Diagram 1 4" Speaker Polar Plot 2 kHz Octave Band, Grid Spacing = 6dB/Division

Software Options

- **No software**: External software is not required for atomic timekeeping and sending text messages from the device's web server. The devices can operate stand-alone. However, application software can be used to augment the devices capabilities and integrate the device into a mass notification system, on the phone network, etc.
- AND Clockwise: Instantly finds all of your AND devices, it is a clock/alarm program for scheduling, alarms, events, stopwatch, timer, optional theme sound library, sending News/RSS/Twitter/Weather/Stock feeds, etc.
- Third Party Software: AND has a long-standing relationship with InformaCast (SingleWire), and also supports IPSession (IPCelerate), SA-Announce (Syn-Apps), MessageNet Systems, BellCommander (AcroVista), and others. AND devices will also work with SIP-compatible products/PBX, such as Asterisk, 3CX, ShoreTel, etc.
- Multiple: Can run Clockwise and 3rd party software concurrently.

