

2N BlueTower Basic Unit - CPU, PSU, AUX , 2 port PRI GSM Gateway (507310E/2)



Product Name: 2N BlueTower Basic Unit - CPU, PSU, AUX , 2 port PRI GSM Gateway (507310E/2)

Manufacturer: 2N Telecommunications

Model Number: 507310E/2

2N BlueTower Basic Unit - CPU, PSU, AUX , 2 port PRI GSM Gateway (507310E/2)

2N® BlueTower (8 simultaneous calls) - Multichannel GSM Gateway connecting ISDN PRI or VoIP to a GSM network. A company (small, SME) can make significant savings on calls from landlines to cell phones when using this group of products. It is an ideal product for small Call centers where calls are made to GSM networks: reduces call costs by 40-70%! Benefits from customers:

- Least Cost Routing
- SMS sending/receiving
- CallBack (SMS & Voice)
- SMS at no answer
- Remote control
- Modularity
- Auto Clip Routing
- Antenna splitter
- Free minutes counting
- CDR

Usage:

- As GSM Gateway
- Termination/Origination tool
- Back up solution in case of a PSTN line failure
- Routing Gateway
- SMS/CallBack Gateway

More information: 2N® BlueTower is an up to 8-channel PRI (E1)/VoIP GSM Gateway (Fixed Wireless Terminal). It's an ideal solution for medium size enterprises with a dense call traffic to GSM networks. The 2N® BlueTower reduces dramatically the costs of calls from fixed to mobile networks. This 2N GSM Gateway converts fixed-to-mobile or mobile-to-fixed calls into much cheaper mobile-to-mobile calls. Thanks to the sophisticated Least Cost Router (LCR), all calls are always routed in the cheapest possible way. With the Dynamic Clip Routing feature, incoming calls are always routed to the right extension according to a flexibly changing number database. Two ISDN PRI interfaces allow you to install the device between the PBX and PSTN. This eliminates the need to install an additional PRI port over your PBX. Moreover, you need not reconfigure your PBX, which is very useful especially if your PBX is rather obsolete or you don't know its configuration tools well. In case you use VoIP in your company infrastructure you can equip 2N® BlueTower with VoIP card. 2N® SMS Server - a network application for SMS sending and receiving - is one of additional software which provide 2N® BlueTower users another communication tool. The delivery status of any messages is obtained automatically. The 2N® BlueTower PRI GSM Gateway is the most professional and complex device for the corporate segment. For large companies we recommend multichannel 2N GSM Gateways. To get more information about 32 channels solution go to 2N® StarGate PRI GSM Gateway or 16 channels solution go to 2N® BlueStar PRI GSM gateway. Features:

- Up to 8 GSM channels - scalable capacity
- Up to 2 PRI ISDN interfaces
- VoIP interface 2N® BlueTower PRI GSM Gateway

2N BlueTower Basic Unit - CPU, PSU, AUX , 2 port PRI GSM Gateway (507310E/2)

- Efficient Least Cost Routing (LCR) according to free minutes, prefixes, time...
- SMS & Voice Callback
- SMS at no answer
- SMS server - SMS sending & receiving support
- Support of external number portability database
- Call statistics and 100% control of all calls
- GSM network monitoring
- Optionally integrated antenna splitter
- Comfortable remote control and maintenance
- Correct tone detection
- Worldwide use (all frequencies are supported)
- TBR4 certified

HW compatible with the 2N® BlueTower PRI GSM gateway 2N® BlueTower inter works with all PBXs equipped with an E1 ISDN interface (port). 2N® BlueTower is typically used by our clients together with the following brands and products such as: Cisco equipment Quintum systems, etc.

Price: £1,363.50
