2N Helios IP Force - 4 Button + 10W Speaker (9151104W)



Product Name: 2N Helios IP Force - 4 Button + 10W Speaker (9151104W)

Manufacturer: 2N Telecommunications

Model Number: 9151104W

2N Helios IP Force - 4 Button + 10W Speaker (9151104W)

The 2N Helios IP Force 4 button model is an exceptionally sturdy IP intercom that will ensure you effortless communication with the people coming to your door, in combination with reliable security for your building entrance. It supports voice and video communication using the SIP protocol and can deal with the most demanding conditions.

2N Helios IP Force 9151104W Key Features

- The most resistant intercom on the market
- · High-quality audio
- · Easy remote administration
- · Access control by a call, code, or card
- External sources / PoE supply
- · Extensive interface and installation options

2N Helios IP Force 9151104W - Technical Specifications Mechanical Features

- · Maximal resistivity against dust, water, and mechanical damage
- High clarity and volume in noisy environments
- · Illuminated buttons and backlit keyboard
- Integrated RFID card reader

Benefits

- Secure admission to the building of authorised people at selected times
- Entrance monitoring and following the movement of people
- Interconnecting with other security systems in the building
- Easy installation and integration into the existing LAN

Target Groups

- Business: offices, shopping areas
- · Education: universities, campuses, schools, sports areas
- Healthcare: hospitals, laboratories
- Logistics & Dransportation: airports, parking lots or garages
- · Government: prisons
- Industries: Manufacturing & Description, Energy, Metal & Description, Chemicals

Power Supply

- 802.3af (PoE) 48 V / 380 mA DC or
- Adaptor 230 V10%, 50/60 Hz / 12V DC DC power supply 12 V / 1A DC

VoIP

- Signalization SIP
- Number of voice channels 2
- Audio Codecs G.711, G.729

Interfaces

2N Helios IP Force - 4 Button + 10W Speaker (9151104W)

- Ethernet Connector RJ-45 Ethernet speed 10/100 BASE-T
- Reley outputs Maximal voltage 30 V DC, Maximal current 1 A DC

Audio & amp; Video

• Audio 2 integrated microphones, Fullduplex (AEC)

Other

- Dimensions 217x109x83 mm (h×w×d)
- Weight max. 2000 g
- Operating temperatures from –40 to +55 ºC
- Cover level IP65, IP69

Please Enquire