

Product Name: 2N Helios IP Force with HD Camera - 1 Button (9151101C) Manufacturer: 2N Telecommunications Model Number: 9151101C

2N Helios IP Force with HD Camera - 1 Button (9151101C)

The 2N Helios IP Force with HD Camera - 1 Button (9151101C) is an exceptionally sturdy IP intercom that will ensure you effortless communication with the people coming to your door, in combination with reliable security for your building entrance. It supports voice and video communication using the SIP protocol and can deal with the most demanding conditions. 2N Helios IP Force with HD Camera Key Features

- The most resistant intercom on the market
- High-quality audio
- Easy remote administration
- · Access control by a call, code, or card
- External sources / PoE supply
- · Extensive interface and installation options

2N Helios IP Force now provides even more reliable security for entrances to premises than before thanks to the new HD camera. The camera achieves considerably higher resolution in comparison to intercoms with an ordinary camera. Video communication is now of much higher quality and your picture is a lot clearer. The angle of the HD camera remains the same. This new option of an intercom with an HD camera also enables intelligent switching between daytime and nighttime settings. The new intercom is therefore capable of adapting to the conditions at any time of the day. Its main asset is improved night vision with infrared lighting. You will appreciate the HD camera mainly at night when it gives you a clear vision of everything going on in the vicinity. This is how it protects your house from vandalism and burglary. In addition, all certifications are also valid for the new variant, i.e. tests for IP69K rating and tests of resilience to vandalism and IK10 tests.

2N Helios IP Force with HD Camera - Technical Specifications Mechanical Features

- · Maximal resistivity against dust, water, and mechanical damage
- · High clarity and volume in noisy environments
- Wide-angle colour camera with night vision
- Illuminated buttons and backlit keyboard
- Integrated RFID card reader

Benefits

- · Secure admission to the building of authorised people at selected times
- Entrance monitoring and following the movement of people
- Interconnecting with other security systems in the building
- Easy installation and integration into the existing LAN

Target Groups

- Business: offices, shopping areas
- Education: universities, campuses, schools, sports areas
- Healthcare: hospitals, laboratories
- · Logistics & amp; Transportation: airports, parking lots or garages
- Government: prisons
- Industries: Manufacturing & amp; Production, Energy, Metal & amp; Mining, Chemicals

Power Supply

- 802.3af (PoE) 48 V / 380 mA DC or
- Adaptor 230 V10%, 50/60 Hz / 12V DC DC power supply 12 V / 1A DC

VoIP

- Signalization SIP
- Number of voice channels 2
- Audio Codecs G.711, G.729
- Video Codecs H.264, 64 2048 kbit/s H.263+

Interfaces

- Ethernet Connector RJ-45 Ethernet speed 10/100 BASE-T
- Reley outputs Maximal voltage 30 V DC, Maximal current 1 A DC

Audio & amp; Video

- Audio 2 integrated microphones, Fullduplex (AEC)
- 10W D-Class amplifier
- Video Camera 640 (H) x 480 (V), View angle 135° (H), 109° (V), IR Night Vision

Other

- Dimensions 217x109x83 mm (h×w×d)
- Weight max. 2000 g
- Operating temperatures from –40 to +55 ºC
- Cover level IP65, IP69

Price: £721.50