

2N Helios IP Indoor Touch - 91378355

Product Name: 2N Helios IP Indoor Touch - 91378355

Manufacturer: 2N Telecommunications

Model Number: 91378355

2N Helios IP Indoor Touch - 91378355

The elegant 2N Helios IP Indoor Touch - 91378355 constitutes a professional door communication system. By merely looking at the display you can see who is standing at your door, and you can easily conduct a conversation with your visitor if you want, unlock the door and turn on the lights in the corridor or entry hall by using the buttons on the touch display.

2N Indoor Touch Lite Key Features

- Luxury solution to door communication
- Simple control
- Simple configuration
- Comprehensive door communication system
- Retail & SOHO
- Small and Medium Enterprise
- Large Multinational Corporation
- State administration
- Modern interiors
- Representative company areas
- Luxury apartment complexes
- Villas

Product highlights: Using the 2N Indoor Touch multifunctional communicator, you can also monitor video from the camera built into the intercom and have a constant view of what's happening in front of your building. In addition, it allows you to take calls in up to 3 places in your flat.

Overview

The 2N Indoor Touch multifunctional communicator provides audio and video communication with 2N Helios IP intercoms via SIP 2.0 protocol. In addition, it offers simple and intuitive control using a touch screen with an energy saving mode. An integrated microphone, two speakers for effective communication with visitors, and power from an external source, come as standard. If you are interested in modern design and like to invest in stylish items, the silver 2N Indoor Touch panel is designed specially for you. You will not only appreciate its technical features, but the combination of luxury and cutting-edge workmanship will give your interior a stylish touch.

2N Indoor Touch - Technical Specifications

Signalling protocol

- SIP

User interface

- Control: touch panel 15:9
- Display: 800x480px 24bpp (16.7 million colours) with energy saving mode

Audio

- Microphone: Integrated
- Speaker: 2x 1.5W

Video

- Protocols: RTSP, MJPEG/HTTP



- Intercom supervision and control: Yes
- IP camera supervision: Yes

Interface

- Power: 12V DC, typically 6W, maximum 15W, adapter is included in package
- LAN: Ethernet 10/100BASE-T interface, RJ45
- Recommended cabling: Cat-5e or better

Mechanical properties

- General: Flush installation in wall
- Operating temperature: 0°C to 50°C
- Operating relative humidity: 10%-90% (non-condensing)
- Storage temperature: -20°C to 70°C
- Dimensions: 228 x 156 x 45.5 mm – unit 200 x 130 x 60 mm – recessed box
- Weight: 750 g (without frame)

Please Enquire
