

2N NetSpeaker Lite



Product Name: 2N NetSpeaker Lite

Manufacturer: 2N Telecommunications

Model Number: 914013E

2N NetSpeaker Lite

Inform your customers easily

Use the revolutionary 2N® NetSpeaker Lite IP audio system for audio distribution in shops, restaurants and fitness centres. It not only allows you to effectively broadcast advertising messages and audio announcements, but also to play background music from any source. IP technology allows you to distribute audio from one central location to any remote destination or branch, and so you won't be limited to a source of music simply at the broadcasting location.

2N NetSpeaker Lite Key Features

- Effective broadcasting of advertising messages
- Streaming audio online over the IP network
- Ability to create separate zones
- Simple connection for up to 10,000 unique localities
- Central management
- Back-up solution in case of outage
- Simple, quick installation (plug&play)
- Simple, comfortable operation
- Small and Medium Enterprise
- Large Multinational Corporation
- System Integrator
- State administration
- Retail chains
- Supermarkets
- Restaurants and cafés
- Shopping centres
- Wellness and fitness centres
- Manufacturers of amplifiers (as an OEM product)

Product highlights:

With the 2N® NetSpeaker Lite, you get a comprehensive PA solution for commercial premises, which allows you to effectively broadcast advertising messages to any shop, even kilometres away. Thanks to central administration, you also have control of played content, and after dividing branches into zones according to your own criteria, you will be able to send different marketing messages or music to each zone.

Overview

Simply connect the 2N® NetSpeaker Lite to a conventional amplifier capable of powering the connected speakers in order to play audio over an IP network, for example, across the entire shop. You can create a separate zone using any 2N® NetSpeaker Lite, where you can then play various audio content according to your precise requirements. The audio signal is then streamed to various units from a central server, either as unicast (a stream generated for each unit) or multicast, which can be received by all units in the network.

With the 2N® NetSpeaker Lite you not only get greater control of the audio content played in the shop, but you also save on costs for the continuous rental of an audio solution, which is usually supplied by the content provider. An invaluable benefit is the backup solution using a microSD card, where audio from the local 2N® NetSpeaker Lite unit starts to play if there is a data connectivity outage. In addition to this, you will appreciate the ability to use a planner, for example, for announcing advertising messages or information on closing times.

2N NetSpeaker Lite - Technical Specifications

Dimensions and weight

2N NetSpeaker Lite

- Dimensions 105 x 34 x 86 mm
- Dimensions with L-profiles 130 x 34 x 86 mm
- Weight 300 g

Earphone/line out

- 1x Stereo 3.5mm jack on front panel

Digital interface

- Digital output 1x Relay output 24V 1A AC/DC galvanic insulation
- Digital input 1x Digital input 5 to 24V DC no galvanic insulation

Audio properties

- Audio compression MPEG-1 Audio Layer II (MP2)
- Bandwidth 32-320kbps

Power

- Power from external source 12V DC / 2A

Playback backup

- MicroSD card max. size 32GB

Price: £250.80
