

# 2N NetSpeaker Presentation Case 914000E



Product Name: 2N NetSpeaker Presentation Case 914000E

Manufacturer: 2N Telecommunications

Model Number: 914000E

Availability: In stock

2N NetSpeaker Presentation Case 914000E

The 2N NetSpeaker Presentation Case is for the 2N NetSpeaker IP audio system, loud speaker, POE Injector and Remote Control.

For audio transmission over IP all you need to do is connect a standard speaker or amplifier to the 2N NetSpeaker, thus creating a virtual central broadcasting system. This allows for any audio to be played with the options to create separate zones with different communication content. A use for this solution is found, for instance, in schools, shopping centres, office buildings, at train stations, in athletic, cultural or health facilities and in many other public spaces.

- The system configuration

- 2N® NetSpeakers settings
- The zones creating
- Audio inputs administration
- Audio relations creating
- Events planning
- Users management

2N NetSpeaker Presentation Case 914000E Technical Specifications

Dimensions & Weight

- Dimensions 105 x 34 x 86 mm
- Dimensions (incl. L-profiles) 130 x 34 x 86 mm
- Weight 300 g

Amplifier parameters

- Power amplifier output 4 terminals on back panel Stereo/Mono with auto detection
- Loudspeaker impedance 4-16Ω
- Frequency range 20Hz – 20kHz (+/- 0.5dB)
- Harmonic distortion 0,05% @ 1kHz
- Signal-to-noise ratio 91dB
- Headphones/Line out 1x Stereo 3,5mm jack on front panel

## Digital Interface

- Digital output 1x relay output 24V 1A AC/DC galvanically isolated
- Digital input 1x digital input 5 to 24V DC galvanically non-isolated

## Audio parameters

- Sound compression MPEG-1 Audio Layer III (MP3)
- Bandwidth 32-320kbps

## Power supply

- External power supply 12V DC / 2A
- LAN power supply PoE IEEE 802.3af

**Price: £414.30**

---