

# 2N NetSpeaker with loud speaker set (NSp server SW included) 914020E



Product Name: 2N NetSpeaker with loud speaker set (NSp server SW included) 914020E

Manufacturer: 2N Telecommunications

Model Number: 914020E

Availability: In stock

2N NetSpeaker with loud speaker set (NSp server SW included) 914020E

2N NetSpeaker inbuilt loudspeaker version For audio transmission over IP all you need to do is connect a standard speaker or amplifier to the 2N NetSpeaker, thus creating a virtual central broadcasting system. This allows for any audio to be played with the options to create separate zones with different communication content. A use for this solution is found, for instance, in schools, shopping centres, office buildings, at train stations, in athletic, cultural or health facilities and in many other public spaces.

- The system configuration

- 2N® NetSpeakers settings
- The zones creating
- Audio inputs administration
- Audio relations creating
- Events planning
- Users management

2N NetSpeaker + loud speaker set (NSp server SW included) 914020E Technical Specifications

Dimensions & Weight

- Dimensions 105 x 34 x 86 mm
- Dimensions (incl. L-profiles) 130 x 34 x 86 mm
- Weight 300 g

Amplifier parameters

- Power amplifier output 4 terminals on back panel Stereo/Mono with auto detection
- Loudspeaker impedance 4-16Ω
- Frequency range 20Hz – 20kHz (+/- 0.5dB)
- Harmonic distortion 0,05% @ 1kHz

## 2N NetSpeaker with loud speaker set (NSp server SW included) 914020E

- Signal-to-noise ratio 91dB
- Headphones/Line out 1x Stereo 3,5mm jack on front panel

### Digital Interface

- Digital output 1x relay output 24V 1A AC/DC galvanically isolated
- Digital input 1x digital input 5 to 24V DC galvanically non-isolated

### Audio parameters

- Sound compression MPEG-1 Audio Layer III (MP3)
- Bandwidth 32-320kbps

### Power supply

- External power supply 12V DC / 2A
- LAN power supply PoE IEEE 802.3af

**Price: £375.70**

---