

2N SingleTalk Lift Entry Device



Product Name: 2N SingleTalk Lift Entry Device

Manufacturer: 2N Telecommunications

Model Number: -

2N SingleTalk Lift Entry Device

The 2N SingleTalk represents a suitable solution for two-way emergency communication from the lift cabin in line with the valid European standards and can be connected to the lift by means of a PSTN/PBX/GSM line.

2N SingleTalk Key Features

- TÜV certified (EN 81-28, 70 compliant)
- Connection possibly via PSTN/GSM/PBX
- Two-way communication between the machine room and the cabin
- Fully supplied from the telephone line
- Voice menu for easy programming
- Up to 6 phone numbers in case of emergency
- Small and Medium Enterprise
- Large Multinational Corporation

2N SingleTalk Specification - Technical Specifications

Supplementary Features

- Up to 6 predefined emergency numbers
- Voice menu for easy programming
- Fully automatic function

2N SingleTalk; CallConnect

- Communication from machineroom to cabin
- Local programming of 2N SingleTalk
- Possible communication with cabin even during phone line communication

2N SingleTalk; LiftManager

- PC keeping eye on your lift

Receiving of:

- DHCP Client/Server
- DHCP Options
- Dynamic DNS Service Updating
- NTP Client
- DNS Cache/Proxy
- Static Routing

NAT (IPv4):

- Alarm calls
- Error messages
- Control calls
- Integrated database of companies & customers
- Registration of incoming calls
- Automatic operation

Please Enquire

VoIPVN <http://voip.com.vn>