

ACTi E926 10MP Outdoor Mini Dome with D/N, Adaptive IR, Basic WDR, M12 connector, Fixed lens



Product Name: ACTi E926 10MP Outdoor Mini Dome with D/N, Adaptive IR, Basic WDR, M12 connector, Fixed lens

Manufacturer: -

Model Number: E926

ACTi E926 10MP Outdoor Mini Dome with D/N, Adaptive IR, Basic WDR, M12 connector, Fixed lens

The E926 10MP IR Day/Night Outdoor IP Dome Camera with 1-Way Audio Support & 3.6mm Lens from ACTi is capable of recording images up to 1920 x 1080 at 30 fps and up to 3648 x 2736 at 7 fps. It uses H.264 HP, MJPEG compression formats for storing images. This camera is IK10 (vandal-resistant) and IP68 (weatherproof) rated for installation in high-risk areas. The day/night functionality and a mechanical IR cut filter allow recording in color with illumination levels as low as 0.1 lux. When the illumination levels go below 0.1 lux, the camera switches to night mode and can record clear images up to 49.2' with the help of adaptive IR LEDs. This camera supports 1-way audio communication and features a microSDHC/SDXC memory card slot for local storage.

ACTi E926 Key Features

- Product Type : Mini Dome
- Maximum Resolution : 10MP
- Application Environment : Outdoor
- Day / Night : Yes
- Low Light Sensitivity : Standard
- IR LED : Yes, Adaptive IR (Adjustable IR Exposure Compensation)
- Lens : Fixed focal, f3.6mm / F1.8, Fixed iris, Fixed focus
- Maximum Frame Rate vs. Resolution : 30 fps at 1920 x 1080
- Wide Dynamic Range : Basic WDR (70 dB)
- Local Storage : MicroSDHC/MicroSDXC

ACTi E926 - Technical Specifications
General

- Product Type Mini Dome
- Maximum Resolution 10MP
- Application Environment Outdoor
- Image Sensor Progressive Scan CMOS
- Day / Night Yes
- Low Light Sensitivity Standard
- Minimum Illumination Color: 0.1 lux, B/W: 0 lux (IR LED on) at F1.8
- Mechanical IR Cut Filter Yes
- IR LED Yes, Adaptive IR (Adjustable IR Exposure Compensation)
- IR Working Distance 15m
- Lens Fixed focal, f3.6mm / F1.8, Fixed iris, Fixed focus
- Viewing Angle Adjustment Pan: 0°~90°;
- Tilt: 0°~90°;
- Lens Mount Board mount
- Horizontal Viewing Angle 101.4°;
- Compression H.264 (Baseline/ Main/ High profile), MJPEG
- Maximum Frame Rate vs. Resolution 7 fps at 3648 x 2736 7 fps at 3648 x 2160 7 fps at 2592 x 1944 7 fps at 2048 x 1536 30 fps at 1920 x 1080 30 fps at 1280 x 720 30 fps at 800 x 600 30 fps at 640 x 480 15 fps at 320 x 240
- Horizontal Resolution (TV lines) 1450 TVL

ACTi E926 10MP Outdoor Mini Dome with D/N, Adaptive IR, Basic WDR, M12 connector, Fixed lens

- Multi-Streaming Dual streams
- Wide Dynamic Range Basic WDR (70 dB)
- Digital Noise Reduction 2D+3D DNR
- S/N Ratio 52 dB
- Audio 1-way (Mic-in, Line-in)
- Network Protocol & Service TCP, UDP, HTTP, HTTPS, DHCP, PPPoE, RTP, RTSP, IPv6, DNS, DDNS, NTP, ICMP, ARP, IGMP, SMTP, FTP, UPnP, SNMP, Bonjour
- Network Connector RJ-45
- Digital Input/Output No
- Local Storage MicroSDHC/MicroSDXC memory card slot (card not included)
- Power Source PoE Class 2
- Environmental Casing Weatherproof (IP68); Vandal proof (IK10); Vibration proof (EN50155)
- Bundled Accessories No
- Mount Type Surface, Gang Box
- Software Based Analytics (require PC based Smart Search Tool, IVS Server or ALPR Server) Face Detection, Motion Detection, Tamper, People Counting, Line crossing, Enter area, Exit area, Appear in area, Missing object, Unattended object, Crowd detection, Forbidden direction, Vehicle Counting, Heat Map, License Plate Recognition, Speed Detection
- Client PC Operating System Windows 7, Windows Server 2008, Windows Vista, Windows Server 2003, Windows XP
- PC Web Browser IE 8, IE 9, IE 10, IE 11, Firefox with VLC, Chrome with VLC, Safari with Quicktime
- ONVIF Compliant Yes
- Starting Temperature -20°C ~ 50°C (-4°F ~ 122°F)
- Operating Temperature -20°C ~ 50°C (-4°F ~ 122°F)
- Approvals CE, FCC, IP68, IK10, NEMA 4X, EN50155, UL (for optional PoE injector)
- Warranty 3 Years

Price: £427.00
