

# AVer E5016 HD NVR



Product Name: AVer E5016 HD NVR

Manufacturer: AVer

Model Number: E5016

## AVer E5016 HD NVR

The AVer E5016 full HD NVR leads the way for a new generation of high performance, cost-effective network recorders, designed to achieve exceptional image quality and excellent reliability. The E5016 supports up to 5 megapixels per channel and a total of 32 megapixels for all channels. It offers PC-like preview performance (2M @ 120fps) and an impressive throughput rate of 120 Mbps, recording all 16 channels using tri-codec compression

### AVer E5016 Key Features

- supports up to 16 IP cameras (network cameras)
- supports H.264 / MJPEG / MPEG-4 compression (tri-codec)
- PC-like preview performance of 2M @ 120fps
- excellent recording performance with up to 120 Mbps throughput rate
- 4 removable HDD trays with internal RAID support (levels 0,1)
- e-SATA interface for extended hard disk or RAID storage
- multiple output support including HDMI, VGA and TV out
- seamless AVer IP cameras integration for remote settings like Smart Stream, ROI, MFZ
- standardized intuitive GUI, identical for local site (DVR/NVR) and remote site (CMS)
- supports easy POS integration without additional data processing devices
- advanced alarm management with multiple event conditions and trigger actions
- embedded smart tools like HDD calculator for quick estimation of expected recording time
- remote software integration: CMS &ndash; CM5000, mobile access applications &ndash; iViewer for iPhone & iPad, AndroidViewer for
- Android smartphones and tablets

### AVer E5016 - Technical Specifications system

- operating system embedded Linux
- total channel number 16
- max. IP camera input 16

### performance

- display 2M @ 120fps
- recording resolution up to 5 megapixels per channel, and a total of 32 megapixels for all channels in H.264 / MPEG-4 / MJPEG format
- throughput 120 Mbps
- storage internal HDD capacity 4 SATA HDDs (4 removable HDD trays) internal RAID support yes (levels 0,1) external HDD capacity e-SATA HDD or RAID x 1 iSCSI support - backup internal DVD-RW - (supports external DVD-RW)

### interface

- monitor VGA output 1 (up to 1920 x 1200)
- HDMI output 1 (up to 1920 x 1200)
- TV output 1 (supports multi-quad output)
- spot output -
- audio input via IP camera
- output 1 line-out
- MIC input 1 line-in

- alarm sensor (alarm) input 16
- input voltage: max. DC 6V
- relay output 4 (NO/NC)
- voltage range: AC 125V / DC 30V
- switching current: max. 1A
- network Ethernet (RJ45) 2 (10/100/1000 Base-T)
- connection e-SATA 1
- RS-232 1 (D-sub 9 pins, male)
- RS-485 1 set (Tx+, Tx-, Rx+, Rx-)
- USB 2.0 3 (2 ports on front panel, 1 port on rear panel)

## general

- electrical power input 90W power adaptor, DC 19V
- environmental operating temperature 0&deg;C to 40&deg;C
- operating humidity 90% RH
- mechanical dimensions (W x H x D) 430 x 105 x 410 mm
- weight (net) 8kg

**Price: £1,661.63**

---