

Product Name: AVer HVC130 HD Video Conference System

Manufacturer: AVer Model Number: HVC130

Please note: the AVer HVC130 has been discontinued. The AVer EVC130 is the direct replacement.

AVer's HVC130 HD Video Conference System

The AVer HVC130 gives businesses a budget-friendly video conferencing product for 2way, point-to-point communication. The HVC130 from AVer comes equipped with a 5-megapixel PTZ camera and HD720p30fps output for clear, lag-free video. And, by linking the system's unidirectional microphones into a daisy chain, you can enjoy clear audio in even larger conference rooms. AVer has developed a number of handy software add-ons for the HVC series as well, like ScreenShare, our wireless content sharing software for PCs, and VCLink, our exclusive app for instantly sharing live images and snapshots using your mobile device.

The HVC130 solution is full of great features

The AVer HVC130 HD video conferencing system is budget-friendly, and designed with flexibility and convenience in mind.

AVer HVC130 Key features

- See every expression clearly with the HVC130's HD720P resolution at 1M bandwidth
- Experience crystal clear, lag-free video feed thanks to the 30fps frame rate
- Share and receive content from laptops, visualizers (document cameras) and similar devices while still displaying the live video feed
- Connect with any far-site device supporting the H.323 protocol, and the H.239 protocol for content sharing

HVC130 Technical Specifications: Model HVC130 System includes

- Main system
- HD quality PTZ camera
- Microphone (unidirectional)
- IR remote control
- L-bracket
- Connection cables

Communications

. H.323 and SIP standard

- 128kbps~4mbps
- 1xRJ-45 network LAN (10/100Mbps)
- · Manual bandwidth setting
- MCU up to 4 sites
- Content sharing capability from all sites

### Display

- Supports XGA (4:3 RGB) / 720p (16:9 RGB) display
- Supports single and dual monitor display
- Multiple layout styles
- User-friendly OSD (supports 20 languages: English, Traditional Chinese, Simplified Chinese, Czech, Danish, Dutch, Finnish, French, German, Hungarian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese-Brazil, Russian, Spanish, Swedish, Thai)
- Display / edit site-name

#### Video standards

- H.264, H.263, H.263+, H.261
- H.239 dual video streams

### Video features

- Video conferencing resolutions:
- QSIF (176 x 120) QCIF (176 x 144) SIF (352 x 240) CIF (352 x 288) 4SIF (704 x 480 4CIF (704 x 576) HD720p (1280 x 720)
- Content sharing resolutions:
- VGA (640 x 480) SGA (800 x 600) XGA (1024 x 768) SXGA (1280 x 1024)
- Supports rate control mechanism
- Supports H.239 dual video stream shared from local or remote side

## Camera

- 5-megapixel CMOS camera
- 7X optical zoom
- PTZ function (±25° up/down; ±100° left/right)
- $F = 3.325 \sim 3.675$ ;  $fI = 6 \sim 60 \text{ mm}$
- 30 cm MOD
- 62 degree FOV

## Video inputs

- PTZ camera input
- S-video input
- VGA input (for dual stream content)

#### Audio features

- Echo cancellation
- Auto gain control
- Noise suppression

#### Audio standards

• G.711, G.722, G.722.1, G.728, G.722.1C

## Audio inputs

- AVer MIC input
- Aux. MIC in from mini XLR connector
- RCA audio input

### Audio outputs

- HDMI audio output
- RCA audio output

### Others

- Snapshot images and live images can be shared from your mobile device
- Remote management through Web
- live monitoring function from Web
- Firmware update via Internet / Ethernet or USB flash drive
- Upload and manage phone book via the Internet
- RS-232 interface for API
- Remote control App on iOS & amp; Android
- Phonebook download / upload / edit
- Save system settings

**AVer Product Comparison** 

Product HVC330 HVC130 H300

Recommended Room Size Large Conference Room Large Conference Room Small Room or Office

Standard/industry compliance H.323 & SIP H.323 & SIP

H.323 & SIP

Video resolution HD 720p 30fps

HD 720p 30fps HD 720p 30fps

Camera PTZ camera PTZ camera PTZ camera

Supported Formats 16:9 & 23 16:9 & 25 16:0 & 25 16:0 & 2

Video Connectivity HDMI & WGA HDMI & WGA VGA

Content sharing Wireless & Samp; VGA Wireless & Samp; VGA VGA

Dual display support Yes Yes Yes

Included MICs 2 directional 1 directional 1 omni-directional

MCU Integrated 4-way MCU

Integrated 4-way MCU

Recording and playback Recording & Dayback Playback only Recording & Dayback

Snapshot feature Yes

### Yes

External/Aux MIC support Mini XLR & Samp; 3.5mm Mini XLR & Samp; 3.5mm 3.5mm

RS-232 Support

Yes Yes

Included warranty

3 Years RTB

3 Years RTB

2 Years RTB

Remote API and Web Remote

Yes

Yes

Yes

VCLink Support

Yes

Yes

Yes

**Please Enquire**