

Product Name: AVer SD1306 1.3M Speed Dome IP Camera Manufacturer: AVer Model Number: SD1306

AVer SD1306 1.3M Speed Dome IP Camera

The AVer 1.3-megapixel SD1306 Speed Dome IP Camera supports an array of pan/tilt/zoom (PTZ) capabilities including 360° endless pan and powerful 22X optical zoom allowing users to quickly zero in on a desired area. Thanks to its IP66-rated weatherproof housing offering protection against temperatures as low as -20°C, the SD1306 can be used both indoors and outdoors. A range of advanced features including BLC, WDR, and DNR ensures excellent image quality even under very challenging light conditions. AVer SD1306 Key Features

- 1.3-megapixel 1/3" CMOS sensor with zoom lens (f=4.7~103.4 mm)
- Supports up to 1280 x 1024 at 30 fps
- H.264 / MJPEG / MPEG-4 compression (tri-codec)
- Supports plug and play feature with AVer DVRs/NVRs
- Robust housing with IP66 rating
- Protection against low temperatures (-20°C)
- Precise 22X optical zoom allowing to quickly zero in on a desired area
- Built-in mechanical ICR (IR-cut filter removable) for excellent day and night visibility
- Supports Wide Dynamic Range (WDR) and Digital Noise Reduction (DNR) to deliver cleaner, sharper images in challenging light environments
- Supports Backlight Compensation (BLC) preventing direct strong light from blinding the camera
- Local storage backup (microSD/SDHC card, up to 32GB) when an event is triggered or the
- network is down
- 2-way audio communication
- event trigger actions: mail, FTP, save to memory card, relay, Samba
- NXU Lite video management software (free up to 32CH)

AVer SD1306 - Technical Specifications application environment

- indoor / outdoor indoor / outdoor
- weatherproof IP66
- vandal-proof -
- day / night control auto / manual / schedule

camera image

- sensor 1/3" CMOS min. illumination color: 1 lux @ F1.6
- black & amp; white: 0.05 lux @ F1.6
- built-in IR LEDs -
- IR distance mechanical ICR yes auto iris yes

lens

- lens type 22X zoom lens
- F/no F1.6~F3.1
- focal length f=4.7~103.4 mm
- angle of view 53.0° (W) ~ 4.5° (T) (horizontal) 47.0° (W) ~ 3.4° (T) (vertical)

PTZ control

AVer SD1306 1.3M Speed Dome IP Camera

- pan range 360° (endless)
- tilt range 10° ~ 170°
- manual pan speed 0.45° ~ 90°/s
- manual tilt speed 0.35° ~ 45°/s
- preset positions 256
- preset speed pan & tilt: 200°/s
- auto patrol 8 groups with 24 points

video

compression H.264 / MPEG-4 / MJPEG simultaneously max. resolution (H.264 / MJPEG) 1280 x

- 1024 max. frame rate H.264 / MPEG-4 / MJPEG up to 30fps (1280 x 1024)
- streaming H.264 / MPEG-4 / MJPEG
- multiple streams 3
- WDR (Wide Dynamic Range) D-WDR
- BLC (Backlight Compensation) yes
- DNR (Digital Noise Reduction) 3D
- Smart Stream -
- ROI (Region of Interest) -
- IMD (Intelligent Motion Detection) zone yes
- · privacy mask -
- image orientation mirror, flip, rotate

audio

- audio encoder G.711 / G.726 audio compression
- audio streaming 2-way audio
- microphone external microphone input

network

• protocol HTTP, HTTPS, UDP, TCP/IP (IPv4, IPv6), QoS/DSCP, UPnP, SMTP, FTP, PPPoE, DHCP, DDNS, NTP, 3GPP (video only), Samba, RTSP, SNMP, Access list

- Ethernet Ethernet (10/100 Base-T), RJ45 connector
- security password protection, IP address filtering, HTTPS encrypted data transmission
- users up to 8 users simultaneously

alarm

• trigger event mail, FTP, save to memory card, relay, Samba

interface

- digital input / output 2/1
- built-in storage option microSD / microSDHC card (32GB max.)

general

- power supply AC 24V / PoE
- DC power consumption: 11.52W
- PoE PoE Class 4 (IEEE802.3at)
- power consumption: 12W
- dimensions 219 Ø x 330.7 H (mm)
- net weight 4.5kg (w/ bracket)
- temperature and humidity -20°C ~ 50°C, 20% ~ 80%

• other value-added features -

software

• VMS NXU Lite (free bundle up to 32CH)

• supported languages English, Arabic, Bulgarian, Czech, Danish, Dutch, Finnish, French, German, Greek, Hebrew, Hungarian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Simplified Chinese, Slovak, Spanish, Swedish, Thai, Traditional Chinese, Turkish

Please Enquire

Nur unter