AVer SF2121H-BHR-50 2M Bullet IP Camera



Product Name: AVer SF2121H-BHR-50 2M Bullet IP Camera

Manufacturer: AVer

Model Number: SF2121H-R-BH50

AVer SF2121H-BHR-50 2M Bullet IP Camera

The AVer 2-megapixel SF2121H-BHR-50 bullet type IP camera (network camera) can display up to full HD quality video in real-time. It is designed for both day and night applications with a mechanical IR-cut filter and IR LED illuminator that creates an effective IR distance of up to 50 meters. The Wide Dynamic Range (WDR) and dynamic 3D/2D noise reduction functions allow the FB2028 to deliver vivid images in poor lighting conditions. The FB2028 is protected by an IP68-rated waterproof and dustproof housing and equipped with built-in heater protecting camera against extremely low temperatures.

AVer 2M SF2121H-BHR-50 Key Features

- 2-megapixel and 1/2.7 inch CMOS sensor with vari-focal lens (f=3~9mm)
- supports up to 30fps @ 1920 x 1080 in H.264 / MPEG-4 format
- supports plug and play feature with AVer DVRs/NVRs
- built-in mechanical IRC (IR-cut filter removable) and IR LED (50m) for excellent day and night visibility
- supports dynamic 3D / 2D noise reduction to deliver cleaner, sharper images in low-light environments
- EN50130-4 certified, ensuring high surge and electro-thermal resistance
- local storage backup when an event is triggered or the network is down
- event trigger actions: mail, FTP, save to on-board microSDHC card, relay, Samba
- cable management wall mount for easy installation
- NXU Lite video management software (free up to 32CH)

AVer 2M SF2121H-BHR-50 - Technical Specifications application environment

- indoor/outdoor indoor / outdoor (IP67)
- day/night control auto / manual / schedule

system

- ONVIF compatibility v2.1
- flash (MB) 128
- RAM (MB) 256
- embedded OS Linux

camera image

- sensor 1/2.7" CMOS
- min. illumination color: 0.2 lux @ F1.2
- 0 lux @ F1.2 (IR LED on)
- built-in LED 48-piece IR LED
- IR distance 50m
- mechanical ICR yes
- · auto IRIS yes

lens

- lens type vari-focal lens
- F/no F1.2

AVer SF2121H-BHR-50 2M Bullet IP Camera

- focal length f=3~9mm
- angle of view 121.2°(W)~38.1°(T) (horizontal)
- 62.1°(W)~21.3°(T) (vertical)

video

- compression H.264 / MPEG-4 / MJPEG simultaneously max. resolution (H.264/MJPEG) full HD (1920 x 1080) max. frame rate H.264 / MPEG-4 up to 30fps (1920 x 1080)
- MJPEG up to 24fps (1600 x 1200)
- MJPEG up to 30fps (1280 x 1024)
- streaming H.264 / MPEG-4 (3GPP only) / JPEG
- multiple streams yes
- IMD (Intelligent Motion Detection) zone 3
- WDR (Wide Dynamic Range) yes
- BLC (Backlight Compensation) yes
- noise reduction 3D, 2D
- ePTZ yes
- privacy mask area 3
- image orientation mirror, flip

audio

- audio encoder G.711 / G.726 audio compression
- audio streaming 2-way audio
- · microphone external microphone input

network

- protocol HTTP, HTTPS, TCP/IP, QoS/DSCP, UPnP, SMTP, FTP, PPPoE, DHCP, DDNS, NTP, UPnP, 3GPP (video only), Samba
- Ethernet Ethernet (10/100 Base-T), RJ45 connector
- security password protection, IP address filtering, HTTPS encrypted data transmission
- user up to 10 users simultaneously

alarm

trigger event mail, FTP, save to microSDHC card, relay, Samba

interface

- digital input/output 1/1
- built-in storage option microSDHC card (32G max.)

general

- power supply DC 12V / PoE
- PoE PoE Class 4 (IEEE802.3at)
- power consumption: 7.3W (IR LED off / heater off) 9.4W (IR LED on / heater off) 20.7W (IR LED off / heater on) 22.8W (IR LED on / heater on)
- dimensions 111 W x 114.5 H x 265.2 D (mm)
- net weight 2180g (w/ bracket)
- temperature and humidity -40°C~50°C, 20%~90%

software

AVer SF2121H-BHR-50 2M Bullet IP Camera

- VMS NXU Lite (free bundle up to 32CH)
- support language English, Arabic, Bulgarian, Czech, Danish, Dutch, Finnish, French, German, Greek, Hebrew, Hungarian, Italian, Japanese, Norwegian, Polish, Potuguese, Romanian, Russian, Simplified Chinese, Slovak, Spanish, Swedish, Thai, Traditional Chinese, Turkish

Please Enquire

