

AVer SkyCongress Solo



Product Name: AVer SkyCongress Solo

Manufacturer: AVer

Model Number: AVERSKYCONGRESSSOLO

AVER SkyCongress Solo powered by HVC130 & AVer VCBridge

All-in-One HD Video Conferencing Turnkey System

The AVer SkyCongress Solo is a complete turnkey system for your meeting room. Everything you need for a quality HD video conferencing comes in a convenient set. The AVer SkyCongress Solo is powered by the AVer HVC130 & AVer VCBridge.

- Powered by HVC130 & AVer VCBridge
- 46" digital signage display x 1
- Strong, lightweight, mobile cart
- Smart Video Conferencing up to 11 Sites (SkyCongress Duo only)
- Bringing 1-8 Skype® users into an H.323/SIP with no additional licence fees
- Image sharing & VC control via mobile devices
- Wireless content sharing via PC
- Skype® users can send & receive live video, audio and sharable content during video conferences*
- 5M PTZ (pan-tilt-zoom), 7X Optical Zoom camera

AVER SkyCongress Solo powered by HVC130 & AVer VCBridge
Multipoint call hosting

- point-to-point MCU + 1-8 Skype® contacts

Meeting recording

- no

Snapshot sharing

- no

PC content sharing

- yes (via VGA cable or wireless with ScreenShare)

Tablet & mobile phone integration

- yes (w/ VCLink software)

System integration

- yes (via RS-232 port)

Web-based system management

- yes (w/ WebTool)

AVER HVC130 - Technical Specifications

Package Contents

AVer SkyCongress Solo

- Main system unit (codec)
- HD PTZ camera
- HVC microphone
- IR remote control with batteries
- L-bracket (camera stand)
- Power supply
- Cables
- Warranty card
- Quick guide

Communications

- H.323 and SIP standards
- 128Kbps ~4Mbps
- RJ45 network LAN (10/100Mbps)
- Manual bandwidth settings
- Content sharing capabilities from all sites

Camera

- 5-megapixel CMOS camera
- 7X optical zoom
- ±100° pan; ±25° tilt
- 62° FOV

People video resolutions

- HD720p (1280 x 720)
- 4SIF (704 x 480), 4CIF (704 x 576)
- SIF (352 x 240), CIF (352 x 288)
- QSIF (176 x 120), QCIF (176 x 144)
- All resolutions at 30fps

Content video resolutions

- Supported resolutions:
 - SXGA (1280 x 1024)
 - SXGA (1280 x 960)
 - WXGA (1280 x 800)
 - HD720p (1280 x 720)
 - XGA (1024 x 768)
 - SVGA (800 x 600)
 - VGA (640 x 480)
- Output resolutions:
 - SXGA (1280 x 960)
 - XGA (1024 x 768)
 - SVGA (800 x 600)
 - VGA (640 x 480)

Video Standards

- H.264, H.263, H.263+, H.261
- H.239 dual video streams

Video Inputs

AVer SkyCongress Solo

- PTZ camera
- S-video
- VGA

Video Outputs

- HDMI
- VGA

Audio Standards

- G.711, G.722, G.722.1, G.728, G.722.1C

Audio features

- Auto Gain Control (AGC)
- Advanced noise reduction
- Acoustic echo cancellation (AEC)

Audio Inputs

- HVC microphone
- Line-in (3.5 mm)
- Aux. MIC input from mini XLR connector

Audio Outputs

- Digital audio on HDMI cable
- Line-out (3.5 mm)

Other supported standards

- H.224 / H.281, H.225, H.245, H.323 Annex Q, H.460

User interface

- Supports single and dual monitor display
- Multiple layout styles
- User-friendly OSD (supports 21 languages: English, Traditional Chinese, Simplified Chinese, Czech, Danish, Dutch, Finnish, French, German, Hungarian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese-Brazil, Romanian, Russian, Spanish, Swedish, Thai)
- Display / edit site name

Network

- NAT / firewall traversal
- High Efficiency Lost Packet Recovery (HELPeR®)
- API support via RS-232
- IPv4 and IPv6 support

Web Management tool

- Remote management through the Web
- Live monitoring via the Web
- Firmware update via Ethernet / Internet
- Phonebook download / upload / edit
- Restore system settings

Security

- AES (Advanced Encryption Standard) function
- Password protection for system settings
- Password protection for remote system management

Value-added features

- VCLink mobile application for iOS & Android
- - Complete remote control functionality
- - Snapshot and stored image sharing
- - Streaming image sharing (iOS only)
- Wireless PC content sharing via ScreenShare
- software
- Firmware update via Ethernet or USB flash drive
- Screensaver and auto power off mode
- 2 front panel USB 2.0 ports

Power supply

- AC 100V ~240V, 50/60Hz
- Consumption: DC19V, 3.42A

Environmental data

- Operation Temperature: 0°C ~40°C
- Operation Humidity: 20% ~80%
- Storage Temperature: -20°C ~60°C
- Storage Humidity: 20% ~80%

Physical characteristics

- Package weight: 7.1kg (15.7lbs)
- Main system (codec): 320 x 259.6 x 27 mm
- Camera: 160 x 141 x 89.5 mm
- Microphone: 118 x 116 x 21 mm

Warranty

- 3-year parts and labour†

Please Enquire