

Aastra 610D DECT IP Phone



Product Name: Aastra 610D DECT IP Phone

Manufacturer: -

Model Number: AAST-610D

Aastra 610D DECT IP Phone

Please Note: The Aastra 610D is End of Life. Please see the Aastra 612D as an alternative product.

The Aastra 610D IP Phone is an entry level DECT business phone which is part of Aastra's 600D family. The 610D has a large illuminated "graphic display which makes navigation and browsing through directories easy. Aastra 610D DECT IP Phone Key Features

- LC-display ("; 176 x 160 dots, monochrome)
- Telephone book for 200 contacts*, with 5 possible entries: office, private and mobile number; email address* and ringing tone* assignment
- Headset connector (2.5 mm jack)
- Intelligent battery management
- 2 programmable navigation keys
- Ambient noise filter for loud environments
- 44 polyphone (Midi type) and 8 normal ring tones with automatic volume control can be assigned
- Up to 5 user profiles for e.g. Headset or meeting usage can be configured
- Hands free operation
- 3 colour multi-purpose LED which can be set for signalling numerous operation modes.

The Aastra 610D is compatible worldwide with all Aastra PABXes. Variations for OEM customers are possible and GAP standards for basic functions is supported.

Aastra 610D DECT IP Phone - Technical Specifications

Local Features

- Key lock (shortcut: pound key)
- 3 Soft keys for menu control two of which are programmable
- Ring tone volume adjustable
- Different earpiece-, speaker- and headset volume
- Display with 6 Text lines, 1 headline and 1 soft key line
- Handset name can be edited
- Display contrast adjustable
- Illumination time for display and keypad can be adjusted separately (separate values while in/out of charger)
- Ring tone off (shortcut: Asterisk key)
- Key lock (shortcut: # key)
- Different ring tones for: Internal-, External calls, Messages, Alarm call, Emergency call *
- Signal tones for key click, confirmation, battery empty, out of range
- Dim function for display light
- Alarm and appointment settings for 3 different times each*
- Automatic / Manual key lock
- Telephone lock with 4-digit PIN
- Automatic answer when removed from the charger
- Silent charging
- Caller list with 30 entries*
- Redial list with 20 entries*
- Display languages: German, English, French, Italian, Spanish, Russian, Dutch, Finnish, Swedish, Danish, Portuguese, Norwegian *
- +, - volume keys

- Time and Date (manually or by PABX*)

Administration Features

- Automatic firmware update "over air";*
- Integrated diagnostic functions

Technical Data

- Standards: DECT, GAP
- Ingress protection: IP 50
- Talk time at least 12 h EMEA / 15 h US
- Standard battery: Lithium-Ion battery pack, 850 mAh
- Free fall: 1.5 m on concrete without damage
- Dimensions: length / width / depth 135 x 49 x 22.5 mm
- Weight with Standard battery: 120 g
- International AC Adapter for EMEA, North America and Australia
- Supports DECT-encryption
- Stand-by-time at least 100 h EMEA / 95 h US

* if supported by the PABX

Please Enquire
