

Atcom IP02 Asterisk PBX Appliance



Product Name: Atcom IP02 Asterisk PBX Appliance

Manufacturer: Atcom

Model Number: IP02

Availability: In stock

Please note: An understanding of both Linux and Asterisk command line is required for the successful configuration of the Atcom IP0x. VoIPon offers paid for support options for customers who experience difficulty configuring this PBX, which can be selected from the options below.

The IP02 is the latest member of the IP0x family and is a complete Asterisk Appliance with either one FXO or FXS module. It is an embedded open source Linux system with built-in SIP/IAX proxy server and NAT functions. The IP-02 provides a solid, uniform platform for traditional PSTN communications in addition to VoIP communications. Targeted at SOHO and SMB market with an easy to use graphical interface, the IP02 provides a cost-saving solution on their telecommunication/data needs. With the IP01, company with branch offices in different locations can be easily combined together to work like a virtual single office through the internet. Features: System:

- Open Source uClinux
- Hardware:
- CPU: 400MHz Blackfin 532 Chip
- One analogue (FXO/FXS) module interfaces.
- NAND flash 256 M
- SDRAM 64M

Features:

- Open Source Asterisk IP PBX
- VoipTel GUI (Customised AsteriskNow GUIs)
- High performance OSLEC (Open Source Line Echo Canceller)
- Configurable IVR menu.
- Voice Mail
- Call forward, call waiting, call transfer
- Call conference
- Call queues
- SIP trunking, IAX trunking
- PSTN analogue trunk
- Flexible dial plan
- Configurable IVR menu.

Specification: Interfaces:

- 1 X RJ45 port.
- 1 X Power port.
- 1 X RS232 port.
- 1 X RJ11 ports. (FXS/FXO configurable)
- 1 X FXO/FXS module slot

Accessories:

- Power adaptor
- FXO/FXS modules

Atcom IP02 Asterisk PBX Appliance

Applications:

- SOHO application
- IVR (Interactive Voice Reconition)

Size:

- 100 x 100 x 28 CM

RJ11 Cables If you need RJ11 BT Phone cable or RJ11 with ring capacitor please see the products below: Phone Line cable RJ11 to BT Plug RJ11 Adaptor with Ring Capacitor

Price: £153.00

Options available for Atcom IP02 Asterisk PBX Appliance :

Port 1 - FXO/FXS

- Not Required -, 1 x Dual FXS Module (+£47.00), 1 x Dual FXO Module (+£47.00), 1 x FXO port and 1 x FXS port (+£50.50).

Warranty

IP01/IP02 Additional 12 Month Warranty (+£50.00), IP01/IP02 12 Month Warranty.

Annual Support Maintenance

Require Annual Support (+£480.00), - Not Required -.