

ClearOne MAX-EX Conference Phone



Product Name: ClearOne MAX-EX Conference Phone

Manufacturer: ClearOne

Model Number: CC-910-158-501

ClearOne MAX-EX Conference Phone

The MAX EX conference phone provides premium, full-duplex audio with unmatched expansion capabilities. Integrating ClearOne's industry-leading professional audio technology and advanced processing, MAX EX brings you unbelievable clarity, unique expandability — and incredible ease of use. MAX EX is the perfect solution for small conference rooms as a single unit, and also covers medium to large conference rooms as an expanded system. Link up to four phone units complete with microphones, loudspeakers and controls for an even distribution of sound. With MAX EX in meetings, not only can discussions flow more freely, so can productivity.

- Easy set up and operation — just plug the base station into a power outlet and analog telephone jack
- Automatic Level Control — automatically adjusts microphone volume levels based on how loudly participants in the local room are talking to improve voice quality for far-end participants
- Automatic Gain Control — automatically adjusts loudspeaker volume based on the incoming audio signal from the far end to provide clear, intelligible audio in the local room

Suggested Usage It comes with a single unit conference phone that can be linked with as many as three additional MAX phones (MAX EX Expansion Kit) for use in larger conference rooms



- Small conference rooms — up to 8 people
- Executive offices
- Home offices

MAX EX Expansion Kit

- Larger conference rooms
- Expand capabilities of MAX EX and MAX Attach
- Connect up to 4 total phones

ClearOne MAX-EX Conference Phone Technical Specifications

Echo Cancellation

- Tail time: 60 ms x 3

Noise Cancellation

ClearOne MAX-EX Conference Phone

- Dynamic noise cancellation

Telephone Connection

- Analog PBX or PSTN line
- RJ-11C, -12 dBm nominal

Keypad

- Alphanumeric standard keypad

Loudspeaker

- Volume: 90dBspl A weighted @ 1 ft
- Bandwidth: 200 Hz–3.3 kHz

Record Output

- Connector: 2.5 mm mono audio jack
- Impedance: <1000 ohms
- Bandwidth: 200 Hz–3.3 kHz
- Dynamic range: 60 dB
- THD <.01%

Certifications

- FCC part 15 Class A
- FCC part 68
- UL Certified

Power

- Base unit: Auto-adjusting power module; 100-240 VAC; 50/60 Hz

Environmental

- Operating temperature: 32–118° F(0–48° C)
- Storage temperature: 41–158° F(5–70° C)
- Operating humidity: 15 to 80%
- Storage humidity: 10 to 90%

Dimensions (W x D x H)

- Phone section: 10.5” x 10.5” x 3” (26.7 cm x 26.7 cm x 7.6 cm)
- Base unit: 4.25” x 5.5” x 2.5” (10.8 cm x 14 cm x 6.4 cm)

Weight

- Phone unit: 2.7 lb (1.2 kg)
- Base unit: .6 lb (0.27 kg)
- Shipping: 10 lb (4.5 kg)

Price: £339.20

VoIPVN <http://voip.com.vn>