

CyberData Auxiliary Strobe for CyberData IP Endpoints



Product Name: CyberData Auxiliary Strobe for CyberData IP Endpoints

Manufacturer: CyberData

Model Number: -

CyberData Auxiliary Strobe for CyberData IP Endpoints

The CyberData Auxiliary Strobe is a cost-effective, user-installable option for the latest line of CyberData VoIP products. The Auxiliary Strobe comes with a 2-meter cable that enables the user to connect to a supported CyberData IP endpoint. Power and signaling for the strobe comes from the attached CyberData Endpoint.

Setup of the strobe's blink rates and brightness are through the web interface of the attached CyberData IP endpoint.

CyberData Auxiliary Strobe Key Features

- 2-meter cable
- 5 user blink scenes available
- Meets ADA requirements for telephony signaling and notification
- Activates from a CyberData IP endpoint
- Mailbox message waiting indication
- Web-based setup

CyberData Auxiliary Strobe - Technical Specifications

General Features

- Power Input: Supplied by the supported CyberData VoIP endpoint
- Light power: 90 candela (5-Watt LEDs)
- Flash rate: 4 scenes available
- LED MTBF: 100,000 Hours
- Operating Temperature: -10 degrees C to 50 degrees C (14 degrees F to 122 degrees F)
- Regulatory Compliance: FCC Class A, UL 60950
- Dimension: 5" x 5" x 1.5" (H x W x D)
- Warranty: 2 Year Limited
- Part Number: 011288

Please Enquire
