

CyberData Networked Door Strike Intermediate Relay Module



Product Name: CyberData Networked Door Strike Intermediate Relay Module

Manufacturer: CyberData

Model Number: -

CyberData Networked Door Strike Intermediate Relay Module

As part of a networked security infrastructure, the CyberData Network Relay Module allows monitoring and control of devices that require high current switching. The CyberData Network Relay Module is PoEpowered (802.3af) and provides an encrypted communication method for secure access.

CyberData Networked Door Strike Intermediate Relay Module Key Features

- PoE 802.3af enabled
- AES encryption (up to 256 bit)
- Discoverable by CyberData VoIP products
- Windows setup utility with diagnostics
- Real time clock with event logging function
- 12Amp relay
- NO/NC contacts
- Opto-isolated sense input
- Wall mounting
- Cable strain relief
- Device status LED

Applications include electronic door strikes and other high current machine control. This product directly interfaces to the CyberData line of VoIP products and also provides an interface for third party applications needing to integrate high current monitoring and switching.

CyberData Networked Door Strike Intermediate Relay Module - Technical Specifications

General Features

- Power Input: 5V to 60V DC / 9V to 250V AC
- Ethernet I/F: 10/100 Mbps
- Operating temperature: -10 degrees C to 50 degrees C (14 degrees F to 122 degrees F)
- Relay Voltage/Current: 12A@250VAC 12A@24VDC
- Dimensions: 6.000" x 3.570" x 1.575"
- Warranty: 24 months
- Boxed Weight: 2.0 lbs.
- Part Number: 011270

Please Enquire
