

CyberData Singlewire InformaCast-enabled VoIP Outdoor Intercom (011309)



Product Name: CyberData Singlewire InformaCast-enabled VoIP Outdoor Intercom (011309)

Manufacturer: CyberData

Model Number: 011309

CyberData Singlewire InformaCast-enabled VoIP Outdoor Intercom (011309)

Now supporting Singlewire InformaCast notification messaging as well as a true SIP endpoint, the CyberData Singlewire InformaCast-enabled VoIP Outdoor Intercom (011309) is perfect for settings requiring two-way communication and secure access. The new Weather Shroud (pictured) can be purchased separately for even greater weather protection. With InformaCast notification messaging and supported Fail-over redundancy, the Singlewire InformaCast-enabled Outdoor Intercom can be installed in nursing care facilities, schools and universities, daycare facilities, retail establishments, highway tolls, and more, proving this device is truly a versatile, cost-efficient alternative to old analog intercoms that has the added benefit of Singlewire InformaCast notifications.

CyberData Singlewire InformaCast-enabled VoIP Outdoor Intercom Key Features

- InformaCast compliant
- InformaCast resiliency protocol
- IP rating of IP65
- Supports SRST (Survivable Remote Site Telephony)
- Streamlined case design
- Optional Weather Shroud (pictured) for even greater weather protection
- PoE 802.3af enabled (Powered-over-Ethernet)
- SIP compliant
- Adaptive full-duplex voice operation
- Network web management
- Network adjustable speaker volume and microphone sensitivity
- Network downloadable firmware
- Doubles as a paging speaker: multicast and InformaCast
- Dry relay contact for auxiliary control (controls external power)
- Door closure and tamper alert signal
- Optional Security Torx screws with driver kit

CyberData Singlewire InformaCast-enabled VoIP Outdoor Intercom - Technical Specifications
General

- Ethernet I/F 10/100 Mbps
- Protocol SIP RFC 3261 Compatible and InformCast v4.0 and later
- Power Input PoE 802.3af compliant or 8 to 12 VDC at 1000 mA
- Operating Temperature -40° C to +55° C (-40° F to 131° F)
- Payload Types G711, A-law and µ-law
- Regulatory Compliance FCC Class A, UL 60950
- Dimensions 5” x 5” x 2.5” (H x W x D)
- Warranty 2 years limited
- Boxed Weight 2.0 lbs.
- Part Number 011309 011188 Weather Shroud (sold separately)

Please Enquire