

# CyberData VoIP Paging Amplifier (010965)



Product Name: CyberData VoIP Paging Amplifier (010965)

Manufacturer: CyberData

Model Number: 010965

## CyberData VoIP Paging Amplifier (010965)

Please note that the VoIP Paging Amplifier has been replaced by the V2 VoIP Paging Amplifier. The CyberData SIP-enabled VoIP Paging Amplifier provides an easy method for implementing an IP-based overhead paging system for both new and legacy installations. The Amplifier provides direct drive of a standard Horn speaker and supports a line out connector for connection to an external amplifier. The interface is compatible with most SIP-based IP PBX servers that comply with the SIP RFC 3261. For non-SIP environments, the Paging Amplifier can be configured to listen to multicast address and port number combinations to form paging zones. The Amplifier provides direct drive of a standard Horn speaker and supports a line out connector for connection to an external amplifier. The interface is compatible with most SIP-based IP PBX servers that comply with the SIP RFC 3261. For non-SIP environments, the Paging Amplifier can be configured to listen to multicast address and port number combinations to form paging zones.

Features

- SIP (RFC 3261) compatible
- Dual-speed ethernet 10/100 Mbps
- Web-based configuration
- Web-based firmware upgradeable
- PoE 802.3af enabled
- IGMP
- Line-out connector
- Direct speaker drive

## VoIP Loudspeaker Amplifier Specifications

- Ethernet I/F 10/100 Mbps
- Power Input PoE 802.3af or 110-230VAC PS
- Protocol SIP RFC 3261
- Payload Types G711
- Regulatory Compliance FCC Class B, UL 60950, CE
- Warranty 2 Years Limited
- Dimensions 1.26" x 9.45" x 3.13"
- Part Number 010965
- Output - With one 8-ohm speaker, up to 8 watts output - With external PoE power injector (Part #010867) and one 8 ohm speaker, up to 10 watts output. - With external PoE power injector (Part #010867) and two 8 ohm speakers in parallel, up to 20 watts output.

**Please Enquire**

---