

Cyberoam CR10iNG UTM Firewall

Product Name: Cyberoam CR10iNG UTM Firewall

Manufacturer: Cyberoam

Model Number: CR10iNG

Cyberoam CR10iNG UTM Firewall

The Cyberoam CR10iNG UTM Firewall are Unified Threat Management NG series Next-Generation network security appliances that include UTM security features and performance required for future networks. The NG series for SOHO offer "the fastest UTMs made for SMBs" to small offices. The best-in-class hardware along with software to match, enables the NG series to offer unmatched throughput speeds, compared to any other UTM appliance in this market segment. This assures support for future IT trends in organizations like high-speed Internet and rising number of devices in organizations – offering future-ready security for small office networks.

Cyberoam CR10iNG Administration & System Management Features

- Web-based configuration wizard
- Role-based Access control
- Support of API
- Firmware Upgrades via Web UI
- Web 2.0 compliant UI (HTTPS)
- UI Color Styler
- Command Line Interface (Serial, SSH, Telnet)
- SNMP (v1, v2, v3)
- NTP Support
- Multi-lingual support: English, Chinese, Hindi, French, Japanese
- Cyberoam Central Console/CCMS (Optional)

With Cyberoam NG series, businesses get assured Security, Connectivity and Productivity. The Layer 8 Technology treats User-Identity as the 8th Layer or the HUMAN layer in the protocol stack. It attaches User-Identity to security, which adds speed to an organization's security by offering instant visibility into the source of attacks by username rather than only IP address. Cyberoam's Extensible Security Architecture (ESA) supports feature enhancements that can be developed rapidly and deployed with minimum efforts, offering future-ready security to organizations.

Cyberoam CR10iNG - Technical Specifications

User Authentication

- Internal database
- AD Integration with support for OU-based Security Policies
- Automatic Windows Single Sign On
- External LDAP/LDAPS/RADIUS database Integration
- Thin Client support
- RSA SecurID support
- User/MAC Binding
- SMS (Text-based) Authentication
- Layer 8 Identity over IPv6
- Secure Authentication – AD, LDAP, Radius
- Clientless Users
- Authentication using Captive Portal

Logging/Monitoring

- Real-time Logging and Monitoring
- Log Viewer - IPS, Web filter, Anti-Virus, Anti-Spam, Authentication, System and Admin Events

Cyberoam CR10iNG UTM Firewall

- Forensic Analysis with quick identification of network attacks and other traffic anomalies
- Syslog support
- 4-eye Authentication

IPSecVPNClient**

- Inter-operability with major IPSec VPN Gateways
- Import Connection configuration

Certification

- ICSA Firewall - Corporate
- Checkmark Certification
- VPNC - Basic and AES interoperability
- IPv6 Ready Gold Logo
- Global Support Excellence - ITIL compliance (ISO 20000)

Hardware Specifications

- Memory 1GB
- Storage 4GB

Compliance

- CE
- FCC

Power

- Input Voltage 100-240 VAC
- Consumption 13.2W
- Total Heat Dissipation (BTU) 45

Dimensions

- H x W x D (inches) 1.35 x 8.75 x 6.8
- H x W x D (cms) 3.43 x 22.23 x 17.3
- Weight 1.10 kg, 2.42 lbs

Environmental

- Operating Temperature 0 to 40 °C
- Storage Temperature -25 to 75 °C
- Relative Humidity (Non condensing) 10 to 90%

Price: £228.80
