

Digium Wildcard TE405P PCI ISDN PRI Card (1TE405PF)



Product Name: Digium Wildcard TE405P PCI ISDN PRI Card (1TE405PF)

Manufacturer: Digium

Model Number: 1TE405PF

Digium Wildcard TE405P PCI ISDN PRI Card

Please Note: The Digium Wildcard TE405P has been discontinued. For an alternative, we recommend the Digium TE436 Four Span Digital T1/E1/J1/PRI PCI 3.3V/5.0V Card (1TE436F)

The Digium TE405P is a high-performance, cost effective digital telephony interface card with the power to create a seamless network, interconnecting traditional telephony systems with emerging Voice over IP technologies.

Used in conjunction with Asterisk, the Digium TE405P can be used to deliver a wide range of PBX and IVR services to the network or handset including Voicemail, Call Conferencing, Three-way Calling, and VoIP Gateways. The Digium TE405P is a quad span, selectable T1 (24-channel per port), E1 (32-channel per port), or J1 (24-channel per port) card utilizing Digium's VoiceBus technology. VoiceBus technology allows the Digium TE405P to use an industry standard bus-mastering PCI interface, as found in millions of PCs worldwide, to maximize system compatibility and eliminate system conflicts.

The Digium TE405P supports both voice and data modes on its quad span, for example, the card can support (per port) 12 channels dedicated to voice, routed directly to the Asterisk Open Source PBX, and 12 to data, handled by the underlying Linux operating system, thus eliminating the need for an external router. The Digium TE405P works in 5V PCI slots. The bus-mastering Digium TE405P improves I/O speed over slave-only architectures, resulting in reduced CPU usage and increased card density per server. The cards provide the power to interconnect traditional telephony systems with emerging Voice-over IP (VoIP) technologies.

Target Applications

- Legacy PBX/IVR Services
- Voice-over Internet Protocol (VoIP) services
- Complex IVR Trees
- "Meet-Me" Bridge Conferencing
- VoIP Gateways (supports SIP, H.323 and IAX)
- Calling Card Platforms
- Voice/Data Router (replace expensive routers)
- PRI Switch Compatibility & Network or CPE

By utilizing Digium's TDMoE (TDM over Ethernet) technology, an exclusive Digium process, you can easily connect multiple PCs equipped with the Digium TE405P and achieve voice quality on par with single PBX implementations. Scalability for this product is derived from adding multiple Digium TE405P cards to each individual PC adding additional cards as you need them for your expanding applications. The Digium TE405P supports industry standard telephony and data protocols, including both RBS and Primary Rate ISDN (PRI) protocol families for voice and PPP, Cisco HDLC, and Frame Relay data modes. The board drives both line-side and trunk-side interfaces, including call features. The Digium TE405P supports industry standard telephony and data protocols, including Primary Rate ISDN (both N. American and Euro Standard) protocol families for voice, PPP, Cisco HDLC, and Frame Relay data modes. Both line-side and trunk-side interfaces are supported, as well as advanced call features.

Improving upon the prior models which did not offer expansion capabilities, the Digium TE405P may be combined with Digium's VPMOCT128 echo cancellation module to deliver 128ms of echo cancellation across 128 channels in E1/T1 modes.

The Digium TE405P has been designed to be fully compatible with existing software applications. They are fully integrated with Digium's Asterisk software. The open source drivers for these cards support an API for custom application development. With the combination of

Digium Wildcard TE405P PCI ISDN PRI Card (1TE405PF)

Digium hardware and Asterisk software, numerous telephony configurations are possible. From the traditional PBX to VoIP Gateways, Digium solutions are paving the way for a new generation of worldwide communications.

Digium TE405P Technical Specifications

Hardware

- Ports: 4 x E1/T1/J1 PRI
- Bus Type: PCI 2.2+
- Connector: 5.0V
- Processor: 32-bit 33MHz
- Echo Cancellation: VPMOCT128 (not included)

Minimum Hardware Requirement

- 800-Mhz Pentium III
- 64MB RAM
- Available PCI Slot

Framing Types

- Superframe (D4)
- Channel Associated Signaling (CAS)
- Common Channel Signaling (CCS)

Coding Types

- Alternative Mark Inversion (AMI)
- Bipolar with 8 Zeros Substitution (B8ZS)
- High Density Bipolar of Order 3 Code (HDB3)
- Optional Cyclic Redundancy Check 4 (CRC4)

Primary Rate Interface (PRI) Switch Types

- National ISDN 1 (NI1)
- National ISDN 2 (NI2)
- Nortel DMS100
- AT&T 4ESS
- Lucent 5ESS
- EuroISDN Q.931
- Q.SIG (Limited Support)

Signaling Types

- E&M, E&M E1, E&M Wink
- Feature Group D (DTMF)
- Feature Group D (MF)
- Feature Group D (Tandem Access)
- Feature Group B
- Feature Group C-CAMA
- Feature Group C-CAMA (MF)
- Foreign Exchange Station (FXS) Loop Start, Ground Start, Kewl Start
- Foreign Exchange Office (FXO) Loop Start, Ground Start, Kewl Start
- PRI Network and CPE

Physical

Digium Wildcard TE405P PCI ISDN PRI Card (1TE405PF)

- Dimensions: 12.7x9.53x1.6 cm
- Full-Height: Yes
- Half-length: Yes
- Temperature: 0 to 50° C

Regulatory

- RoHS compliant
- Manufactured in an ISO 9001:2001 certified facility in the United States
- Maintain an MTBF greater than 1 million hours

Note: Finland, Norway and Sweden require that equipment using this product must be located in a Restricted Access Location (RAL).

Please Enquire
