

Dinstar DWG2001 SIP, GSM VoIP Gateway - 1 Channel (DWG2000-1G)



Product Name: Dinstar DWG2001 SIP, GSM VoIP Gateway - 1 Channel (DWG2000-1G)

Manufacturer: Dinstar

Model Number: DWG2000-1G

Dinstar DWG2001 SIP, GSM VoIP Gateway - 1 Channel (DWG2000-1G)

The Dinstar DWG2000-1G GSM VoIP Gateway also known as the Dinstar DWG2001 is a full functions VoIP gateway based on IP and GSM wireless network, which provides a flexible network configuration, powerful features, and good voice quality. It works for carrier grade, enterprise, SOHO, residential users for a cost-effective solution. The Dinstar DWG2000-1G GSM VoIP Gateway provides access of GSM network. With the development of users and telecom service, mobile network and fixed network integration will be steadily increasing. DWG2000-1G provides high quality VoIP service which perfectly meets the requirement.

- Dinstar DWG2001 SIP/GSM gateway with 1 GSM channel
- Applications: SIP IP PBX GSM Trunk, SIP VoIP line Gateway, SMS Server
- Quad-Band GSM 850/900/1800/1900 MHz

Dinstar DWG2001 - Technical Specifications

General

- Dimensions (Length*Width*Height, unit: mm): 113*77.5*24.5
- Weight (unit: kg): 1.6
- Operating temperature (unit: C): 0-40
- Storage temperature (unit: C): -20-70
- Operating humidity: 10%-90%
- GSM/CDMA/WCDMA SIM Ports: 1 channel
- Power input: 220VAC/50Hz/0.2A
- External power input: 12VDC/1A
- Power (unit: W): 4w
- Network interface: 10/100BASE-TX
- Number of WAN ports: 1
- Number of LAN ports: 1

Price: £130.00
