

Dinstar DWG2004 SIP, GSM VoIP Gateway - 4 Channels (DWG2000-4G)

VoIPVN <http://voip.com.vn>

Dinstar DWG2004 SIP, GSM VoIP Gateway - 4 Channels (DWG2000-4G)



Product Name: Dinstar DWG2004 SIP, GSM VoIP Gateway - 4 Channels (DWG2000-4G)

Manufacturer: -

Model Number: DWG2000-4G

Please Note: The Dinstar DWG2004 SIP GSM Gateway has been discontinued and been replaced by the Dinstar DWG2000C-4GSM VoIP Gateway

Dinstar DWG2004 SIP, GSM VoIP Gateway - 4 Channel (DWG2000-4G)

The Dinstar DWG2004 is a Quad-band SIP/GSM gateway that supports 4 GSM channels / SIM cards. The DWG2004 works with Asterisk®; based IP PBXs like Elastix®, trixbox®, and AsteriskNOW®, as well as other Open Source and proprietary SIP based IP PBXs, Switch, IVR, and VoIP gateway applications.

- Dinstar DWG2004 SIP/GSM gateway with 4 GSM channels
- Applications: SIP IP PBX GSM Trunk, SIP VoIP line Gateway, SMS Server
- Quad-Band GSM 850/900/1800/1900 MHz

Specification

- Dimensions (Length*Width*Height, unit: mm): 113*77.5*24.5
- Weight (unit: kg): 1.6
- Operating temperature (unit: C): 0-40
- Storage temperature (unit: C): -20-70
- Operating humidity: 10%-90%
- GSM/CDMA/WCDMA SIM Ports: 1 channel
- Power input: 220VAC/50Hz/0.2A
- External power input: 12VDC/1A
- Power (unit: W): 4w
- Network interface: 10/100BASE-TX
- Number of WAN ports: 1
- Number of LAN ports: 1

Please Enquire
