Product Name: Elastix ELX025 IP PBX
Manufacturer: Elastix
Model Number: ELX025

Elastix ELX025 IP PBX Appliance
The Elastix ELX025 is a rackmountable chassis IP PBX which offers a 1.8GHz Dual-Core CPU and 2 GB of DDR3 RAM. The 120GB SSD HDD is more than ample to maintain your IP PBX functions. It also features a 10/100 NIC. The basic ELX025 offers a 90W fanless model for low noise and comes with rack mounting ears so it can find a home in your server rack.
Elastix ELX025 IP PBX Key Features

• Up to 12 Analog Ports - We recommend the Sangoma A200 PCI.
• Up to 1 E1/T1/J1 Digital Ports - We recommend the Sangoma PRI Cards and the Sangoma A500 PCI.
• Up to 100 Extensions (SIP/IAX)
• Up to 90 Concurrent calls (max. recommended)

The Elastix ELX025 features Elastix 32 bit version OS preloaded which gives you everything you need for Unified Communications right out of the box. Main features include Auto Attendants, Voicemail, Dial-By-Name Directory, Music on Hold, Multiple Languages, Ring Groups, Call Queue, Call Waiting, Caller Display, Conference Call, Call Hold/Transfer, Call Park, Call Pickup, Automatic Fax Detection, Remote Management, and Remote Extensions.

Elastix ELX025 IP PBX - Technical Specifications
Telephony

• Up to 12 analog ports
• Up to 1 E1/T1/J1
• 1 PCI
• Operating System: Elastix 32 bit (supports 64 bit)
• Up to 100 extensions ((SIP/IAX)
• 90 Concurrent calls (30% CPU usage)
• 50 Recommended concurrent calls

Hardware

• 1.86 GHz Dual-Core CPU
• 2 GB (DDR3) RAM (supports up to 4GB)
• 120GB (SSD 2.5") Hard Disk Drive
• 1 x Gigabit Ethernet
• 2 front panel, 4 back panel USB port

Power Supply

• Rated Power: 90W fanless, efficient PSU
• Operating Voltage: 120/240v Auto switching

Dimensions

• 46 x 437 x 342mm (HxWxD)
• Weight: 4 Kg (8.82lb)

Price: £944.00