

Product Name: Elastix microUCS IP PBX Manufacturer: Elastix Model Number: microUCS

Elastix microUCS IP PBX Appliance

The compact design of Elastix microUCS together with Elastix as a unified communications solution, makes it a powerful IP PBX that allows you to monitor communications in your office or home from anywhere. Easy to install, powerful administration as only Elastix offers and its very low power consumption, make it a very safe and cost effective solution. Elastix microUCS IP PBX Key Features

- Small but robust
- Very low power consumption
- Easy to use, no licensing costs
- Remote management

The microUCS appliance, comes with Elastix preloaded, an Open Source unified communications solution that integrates the best available tools for IP-PBX systems in an easy to use administration interface. Some of the main features are: Auto Attendants, Voicemail, Dial-By-Name Directory, Music on Hold, Multiple Languages, Ring Groups, Call Queue, Call Waiting, Caller Display, Conference Call, Call Hold/Transfer, Call Park, Call Pickup, Automatic Fax Detection, Remote Management, Remote Extensions, and much more.



Elastix microUCS IP PBX - Technical Specifications Telephony

- Operating System: Elastix 32 bit
- Up to 15 extensions ((SIP/IAX)
- 5 Concurrent calls (30% CPU usage)
- 4 Recommended concurrent calls

Hardware

- 400 MHz CPU
- 256 GB RAM
- 8GB (SD) Hard Disk Drive
- 1 x 10/100 Mbps Ethernet
- 1 back panel USB port

Power Supply

- Rated Power: 3W
- Operating Voltage: 110/220v Auto switching

Dimensions

- 28.33 x 165 x 95.8mm (HxWxD)
- Weight: 0.25 Kg (0.55lb)

Price: £200.00