# Elastix miniUCS IP PBX



Product Name: Elastix miniUCS IP PBX

Manufacturer: Elastix
Model Number: miniUCS

## Elastix miniUCS IP PBX Appliance

The Elastix miniUCS appliance, comes with Elastix preloaded, an Open Source unified communications solution that integrates the best available tools for IP-PBX systems in an easy to use administration interface. Some of the main features are: Auto Attendants, Voicemail, Dial-By-Name Directory, Music on Hold, Multiple Languages, Ring Groups, Call Queue, Call Waiting, Caller Display, Conference Call, Call Hold/Transfer, Call Park, Call Pickup, Automatic Fax Detection, Remote Management, Remote Extensions, and much more. Elastix miniUCS IP PBX Key Features

- Up to 8 Analog Ports We recommend the Sangoma A200 PCI.
- Up to 1 E1/T1/J1 Digital Ports or up to 4 BRI We recommend the Sangoma PRI Cards and the Sangoma A500 PCI.
- Up to 50 Extensions (SIP/IAX)
- Up to 32 Concurrent calls (max. recommended)

The miniUCS features an attractive and robust metal housing design, simple and compact which makes it portable and easy to maintain. With only 14W of nominal power consumption, the miniUCS offers significant savings in energy and operating costs, contributing to the conservation of the environment. Thanks to the powerful pre-installed Elastix software, you will have all your business communications fluid and under control.



# Elastix miniUCS IP PBX - Technical Specifications Telephony

- Up to 8 analog ports
- Up to 1 E1/T1/J1 or up to 4 BRI Digital ports
- 1 PCIe
- Operating System: Elastix 32 bit
- Up to 50 extensions ((SIP/IAX)
- 80 Concurrent calls (30% CPU usage)
- 32 Recommended concurrent calls

#### Hardware

- 1.1 GHz CPU
- 1 GB (DDR2) RAM
- 16GB (Compact Flash) Hard Disk Drive
- 3 x Gigabit Ethernet
- 2 back panel USB port

**Power Supply** 

## Elastix miniUCS IP PBX

• Rated Power: 14W

• Operating Voltage: 120/240v Auto switching

## Dimensions

• 56 x 181 x 163mm (HxWxD) • Weight: 0.84 Kg (1.85lb)

Price: £559.00

