

# Epygi QuadroM26xi Hybrid ISDN BRI IP PBX

Product Name: Epygi QuadroM26xi Hybrid ISDN BRI IP PBX

Manufacturer: -

Model Number: QuadroM26xi

Please note that this product has been discontinued. For an alternative we recommend the Epygi IP PBX selection

Epygi QuadroM26xi High Capacity Hybrid ISDN BRI IP PBX Solution  
Migration from a traditional telephone system to Voice over Internet Protocol (VoIP) is now even simpler with the Epygi QuadroM26xi. This solution offers high density analog FXS ports and digital ISDN BRI CO lines for small and medium businesses expanding to VoIP. The QuadroM26xi offers six (6) ISDN BRI trunk ports, 26 FXS analog station ports and up to 80 IP phones. Features & Benefits

- High capacity hybrid solution
- Enterprise-level features
- IP phone flexibility
- Video and HD audio
- Analog phones: 26 IP phones: 16
- Add'l IP phones with keys: up to 80 in blocks of 16, 32 or 64
- Concurrent Calls: 45

Epygi IP PBX

Detailed Comparison Table

|                               | QuadroM26xi | QuadroM26xi-L | QuadroM26xi-S | QuadroM26xi-M | QuadroM26xi-L2 | QuadroM26xi-L3 | QuadroM26xi-L4 |
|-------------------------------|-------------|---------------|---------------|---------------|----------------|----------------|----------------|
| 26 FXS ports                  | 26          | 16            | 16            | 16            | 16             | 16             | 16             |
| 6 ISDN BRI ports              | 6           | 6             | 6             | 6             | 6              | 6              | 6              |
| 80 IP ports                   | 80          | 40            | 40            | 40            | 40             | 40             | 40             |
| 45 Concurrent Calls           | 45          | 45            | 45            | 45            | 45             | 45             | 45             |
| 16, 32, 64 IP ports with keys | 16, 32, 64  | 16, 32, 64    | 16, 32, 64    | 16, 32, 64    | 16, 32, 64     | 16, 32, 64     | 16, 32, 64     |
| Video and HD audio            | Yes         | Yes           | Yes           | Yes           | Yes            | Yes            | Yes            |
| Enterprise-level features     | Yes         | Yes           | Yes           | Yes           | Yes            | Yes            | Yes            |
| High capacity hybrid solution | Yes         | Yes           | Yes           | Yes           | Yes            | Yes            | Yes            |

View Now

## Technical Specifications

### Voice Features

- Voice Coding G.711, G.726 (16, 24, 32, 40 Kbps), G.729A, iLBC (13,33 kbit/s , 15,2 kbit/s); VAD, CNG, G.168 echo cancellation G.722 Pass-through Point-to-Point HD call

### Video Features

- H.263 and H.264 Pass-through Point-to-Point video call

### PBX Features

- Call blocking, Forwarding, Hold, Transfer

- Call relay, Call waiting, Caller
- ID Detection
- Voice mail
- Call park, Pickup, Paging, Intercom
- Multilevel auto attendant with Interactive
- Voice Response (IVR) and VoiceXMLv2 support
- Voice mail with SMS notification
- Distinctive ringing
- Speed dialing
- Many extension ringing
- Receptionist
- Call hunting, Hiding Caller ID
- Automated Call back from Auto
- Attendant
- Hold music
- Call statistics
- Do Not Disturb
- Global speed dial
- Find me/Follow me
- Unified messaging
- 3-way conferencing
- Hotline service
- T.38 fax, fax relay and clear channel fax
- Unified Fax Messaging
- Busy auto-redial
- Directory assistance
- Dial plans (call routing)
- Time of day routing
- Call Queue
- Voice Mail profile
- Automatic Call Distribution
- Conference Server
- Call Recording
- Barge-in

## Supported VoIP Data and Signaling Protocols

- SIP, SIPS/TLS (RFCs: 2246, 3261, 3263, 3265, 3311, 3323, 3324, 3325, 3428, 3515, 3578, 3581, 3725, 3842, 3856, 3863, 3891, 3892, 4028, 4235) SDP (RFC: 2327, 4568) RTP (RFCs: 1889, 1890, 2833, 3389, 3550, 3551, 3555, 3711, draft-ietf-avt-rfc-2833bis-05, draft-ietf-avt-rtp-ilbc-o5), Fax over IP (ITU-T: T.4, T.30, T.38, V.17, V.21, V.27 ter, V.29) Voice Coding (ITU-T: G.711, G.726, G.729 Annex A, RFC 3951 :iLBC; IETF:ITU-T Q.23, Q.24, Bellcore GR.506, GR.181; ITU-T G.168-2000, 2002; ETS\_300659\_1,2,3) ISDN (ITU-T: Q.921, Q.931 (DSS1), Q.951;ETSI ETS300 102 (NET5); NTT INS1500 for Japan)

## POTS

- Loop start, FSK and DTMF Caller ID support

## DTMF

- In band & out of band signaling support

## Physical interfaces

# Epygi QuadroM26xi Hybrid ISDN BRI IP PBX

- Premise connections: 26 FXS short-loop FXS ports (RJ-11) 1 LAN Ethernet 10/100 BASE-T port (RJ-45)
- Uplink connections: 1 WAN Ethernet 10/100 BASE-T (RJ45)
- Uplink connections: 6 ISDN BRI ports to the Central Office or local PBX (RJ45), NT and TE modes supported
- Audio port connections: Line-in/Line-out (Line-in Signal Level- 0,5 V RMS, Line-out Load Resistance - 600 Ohm to 10K Ohm)

## Phones

- IP phones: 16 SIP phones by default 64 additional SIP phones may be added with feature keys
- All SIP phones can be connected both from LAN or WAN side
- Plug-and-Play with select IP Phone manufactures
- Analog phones: 26 Analog phones (or other analog devices) to connect via FXS ports

## Auto Attendants and Virtual Extensions

- Auto Attendants: Up to 200 standard and custom AA can be registered Virtual Extensions: Up to 200 Virtual Extensions can be registered\*

## System Capacity

- Up to 45 simultaneous VoIP calls with external parties
- Unlimited station to station calling for IP phones
- Unlimited station to station calling for analog phones
- 12 ISDN calls with external parties \*The total number of extensions used for
- IP phones, Analog phones, AA and virtual extensions can not exceed 200 extensions.
- External Storage Compact Flash

## Management

- Multilingual WEB interface accessible from LAN and WAN (HTTP/HTTPS)
- Password control
- Remote diagnostics and software upgrade
- Auto-provisioning VoIP Carrier Wizard
- Download/restore configuration
- Legible and editable configuration files
- Auto-configuration of IP phones via TFTP and HTTP
- SNMP Monitoring and Configuration
- Third Party Call Control XML RPC
- Reset button with factory reset option
- Custom Language Pack
- Billing Radius Client (RFCS: 2865, 2866)
- Diagnostics/Testing
- LEDs: Busy, Info, Fault, LAN, WAN, Loop settings Remote testing

## Internet

- STUN/NAT traversal (RFC 3489)
- IPSec VPN with 3DES and AES encryption in tunnel mode. Manual and automatic IKE key support
- PPTP VPN
- L2TP VPN
- Firewall security via: Intrusion Detection System NAT (Network Address Translation)
- Policy and service-based filtering

- Stateful inspection firewall
- DHCP server on the LAN side
- DHCP client on the WAN side
- DNS server with forwarding functionality
- SNTP (Simple Network Time Protocol) server/client for computer clock synchronization PPPoE connection to the ISP with PAP/(MS)CHAP authentication IP DIFFSERV for QoS Virtual LAN (VLAN/IEEE 802.1Q)
- Mail client to send voice and fax messages as e-mail attachments (.wav and .tif) and system notifications
- DNS (DYNDNS) support with third party
- NAT/Router with port forwarding and port translation.

## Physical Dimensions

- Rack-mountable devices: Measurements: 19" x 7.56" x 1.77" (48.0 x 19.2 x 4.5 cm)
- Weight: 2.47 lbs.(1090 g)
- Conditions 41&deg;F - 104&deg;F (5&deg;C - 40&deg;C) operating temperature
- 41&deg;F - 140&deg;F (5&deg;C - 60&deg;C) storage temperature
- 5% - 90% non-condensing humidity
- Power Supply Input 100 - 240 VAC; 50/60 Hz; 0,5 A
- Regulatory Compliance Telecom: TBR3 (ISDN)

**Please Enquire**

---