

# Fanvil i20-T SIP Door Phone



Product Name: Fanvil i20-T SIP Door Phone

Manufacturer: Fanvil

Model Number: i20-T

## Fanvil i20-T SIP Door Phone

The Fanvil i20-T SIP Door Phone is a durable and easy to use SIP Door Entry solution. The Fanvil i20-T features SIP 2.0 and IMS platform of operators, Embedding BRODCOM chip and duplex hands-free, providing voice quality for carrier-class. Fanvil i20-T SIP Door Phone Features

- Supporting SIP 2.0 and IMS platform of operators, and Interconnecting with the mainstream manufacturers IPPBX
- Embedding BRODCOM chip, Stable and reliable
- Duplex hands-free, providing voice quality for carrier-class
- Supporting password to open the door; the RFID card to open the door; the remote to control the door

## Fanvil i20-T SIP Door Phone Technical Specification

- Master Chip Broadcom 1190

### Keys

- Design Stainless steel
- Direct-button 1
- Numeric Keypad Optional

### Voice

- Microphone 1
- Amplifier 1.5W
- Speaker 1.5W
- Volume Control Adjustable
- FDSP Support(AEC)

### Voice stream

- Supportable Protocol RTP
- CODEC G.711, G.729

### Port

- Power Supply 12V+-15%/1A DC or PoE
- PoE PoE 802.3af (Class 0 - 12.95W) 48V/380mA
- LAN 10/100BASE-TX s Auto-MDIX, RJ-45
- Cables HSYV or better
- Passive Switch Normally Open and Normally Closed highest at 30V/1A AC/DC
- Active Switched Output 12V/500mA DC
- RS232 Supported

### RFID/IC Card

- EM-40XX (125Khz) Supported

### Structure

# Fanvil i20-T SIP Door Phone

- Shell Material Aluminum Cover&#12289;Plastic back case
- Operating Temperature -20&deg;C to 70&deg;C
- International Protection IP53
- Working Condition
- Relative Humidity
- 10% - 95%
- Storage Temperature -40&deg;C to 70&deg;C
- Installation Embedded installation (pre-burying)
- Size: Overall Dimension&#65306;174.5&#9587;96&#9587;44mm pre-burying Mounting Dimension&#65306;148&#9587;80&#9587;36mm

**Price: £152.27**

---