

# Fanvil i21T SIP Door Phone



Product Name: Fanvil i21T SIP Door Phone

Manufacturer: Fanvil

Model Number: i21-T

## Fanvil i21T Sip Door Phone IP Intercom

The Fanvil i21T Sip door phone IP intercom offers a smart and effective solution for secure access control and monitoring of a building entrance. Voice transmission is provided by standard IP/RTP/RTSP protocols, which guarantee the best compatibility and integration with third-party IP systems. Features

- SIP V1/V2(RFC2543/RFC3261) and P2P Protocol
- High level of comprehensibility and high volume in noisy environment
- Maximal resistivity against dust, water, and mechanical damage
- A quick dial button and backlit touch keyboard
- Support G.711,G.729,G.722,G.729 etc. Codec voice intercom
- Unlock function (swipe or communication)
- Visitor leave message
- Calling indoor extension for two-way conversation
- Software upgrading on line
- WEB remote management of Terminal malfunction or status

The i21T SIP door phone is designed for operation in the most demanding conditions. The robust mechanical construction offers the highest protective coverage rating against dust and water (IP65) and protection against mechanical damage (Ik10). Numerous deluxe features of the i21T SIP door phone provide high user comfort and guarantee secure access control for any outdoor conditions.

## Fanvil i21T Door Phone Technical Specification

- Master Chip Broadcom 1190

### Keys

- Design Stainless steel
- Direct-button 1
- Numeric Keypad support

### Voice

- Microphone 1
- Amplifier 1.5W
- Speaker 1.5W
- Volume Control Adjustable
- FDSP Support(AEC)

### Voice stream

- Supportable Protocol RTP
- CODEC G.711, G.729

### Port

- Power Supply 12V+-15%/1A DC or PoE
- PoE 802.3af (Class 0 - 12.95W) 48V/380mA
- LAN 10/100BASE-TX s Auto-MDIX, RJ-45&#65289;

# Fanvil i21T SIP Door Phone

- Cables HSYV or better
- Passive Switch Normally Open and Normally Closed highest at 30V/1A AC/DC
- Active Switched Output 12V/500mA DC

## Structure

- Shell Material Stainless steel, cast iron pan
- Operating Temperature -40&deg;C to 70&deg;C
- International Protection IP65 and Ik10
- Working Condition
- Relative Humidity
- 10% - 95%
- Storage Temperature -40&deg;C to 70&deg;C
- Installation wall mounted
- Size Overall Dimension&#65306;230&#9587;125&#9587;76 mm

**Price: £277.27**

---