

Product Name: Gigaset N300IP DECT Base Station & Gigaset R410H Cordless DECT Phones - Three Handset

Bundle

Manufacturer: Gigaset

Model Number: N300IPR410-3

Please Note: The Gigaset R410H has been discontinued.

Gigaset N300IP DECT Base Station & Gigaset R410H Cordless DECT Phones - Three Handset Bundle

The Gigaset N300IP DECT Base Station & Station

- 1 x Gigaset N300IP DECT Base Station
- 3 x Gigaset R410H PRO DECT Phones

The R410H PRO is perfect to use with N720 IP PRO, N510 IP PRO and the Gigaset DX800A All-in-one, a hybrid desktop phone. But it can also be connected to all other Gigaset DECT base stations. Zero-touch installation ensures quick and easy configuration. Key Features of the Gigaset R410H PRO

- Dust and splash water protected (IP 54)
- Shock resistant
- Vibration alert
- Handsfree talking with brilliant sound quality
- Illuminated graphical colour display with 5 lines
- Phonebook for up to 150 names and numbers
- Ergonomic, high quality keypad
- · Easy access to missed call list via illuminated MWI key
- Headset connection via 2.5mm jack

The Gigaset N300 IP is the easy-to-configure hybrid DECT IP base station that lets users enjoy calling over both a landline and the internet. Multi-line support allows registration of up to 6 different compatible Gigaset handsets to the base station and up to 4 parallel calls (1 landline + 3 VoIP) can be made at once. All VoIP calls are in HD sound thanks to exceptional HDSP™ technology. Energy-saving2 ECO DECT means that the Gigaset N300 IP is eco-conscious as well as hi-tech. Features of the Gigaset N300 IP

- Hybrid DECT IP base station for landline and VoIP calls
- Multi-line for up to 6 handsets and 4 parallel calls
- HD sound on VoIP calls1
- Energy-saving2 ECO DECT
- Compatible with multiple Gigaset handsets
- · Compatible with provisioning standards: TR069, MAC address, code based auto-configuration
- Expandable up to 6 VoIP accounts / numbers
- Free calls between Gigaset VoIP phones via Gigaset.net
- Email reader
- Search in net directories and Yellow Pages

Gigaset R410H PRO DECT Phone Technical Specifications Phonebook and Dialing

- Phonebook for up to 150 names and numbers
- Large font available for phonebook entries
- Redialling of last 20 numbers entered
- 9 programmable keys
- Automatic redial function in conjunction with telephone system
- Direct access to outgoing line via off-hook key

Recieving Calls

- Caller indication displayed via CLIP and CNIP
- 15 ringer melodies
- · Individual ringer melodies for VIP entries

Missed Calls

- · Comfortable access to missed call list by dedicated, illuminated MWI key
- List showing up to 30 missed calls with caller indication
- · Direct dialling of the missed call list

DECT Range

Indoor range: up to 50 metersOutdoor range: up to 300 meters

Operation Time

Talk time: up to 12 hours
Standby time: up to 250 hours
Charge time: < 8 hours

Dialing Time

DTMF, pulse

Headset Dimensions

• 151mm (L) x 53mm (D) x 28mm (H), 112g

Green Office

Up to 60% less energy consumption, thanks to an energy-saving power supply

Packaging

- Handset, battery cover for handset, Li-Ion battery, belt clip, charger, power supply for charger, user documentation
- Dimension: 224 mm (L) x 166mm (D) x 60mm (H)
- Overall weight approx.: 340g

Environmental Conditions

- Operating temp: +5 to +45° C
- Storage temp: -15 to +60° C (maximum storage time one week)
- Relative Humidity: 20% -75% non condensating

Siemens Gigaset N300IP DECT Base Station Key Benefits for end-users:

- · Plug & play
- Stand-alone basis
- Multi-line: up to 4 parallel calls (3 VoIP + 1 PSTN calls)
- Multi-user: up to 6 handsets & amp; 6 VoIP accounts/phone numbers
- Exceptional sound quality (HDSP)1), 3)
- Search in online directories (white and yellow pages) 2)
- Access to online information (e.g. emails, weather, eBay companion, encyclopedia, etc)2), 8)

Key Benefits for VoIP Providers:

- Auto-provisioning
- Easy setup
- Software upgrade / Software Downgrade

Basic IP telephony features

- Expandable phone system with multiline functionality for up t6 handsets
- Up t6 SIP accounts from different providers
- Assign SIP accounts individually thandsets (send & Decive direction specifically)
- Multi-Line type system (6 x VoIP + 1 x PSTN) allows: Line selection for each call via menu selection
- Up t4 calls in parallel (3 internet calls + 1 landline calls)
- Easy configuration of internet telephony (VoIP) by wizard and download of provider setting profiles (>200 providers supported)

Enhanced IP Telephony

- Embedded SIP VoIP with codecs: G.711, G.722, G.726, G.729AB6)
- Gigaset.net: free of charge calls between Gigaset VoIP phones. Nickname search in Gigaset.net community.
- Auto-fallback tPSTN, if the phone cannot establish a VoIP connection
- VoIP supplementary services (device controlled): conference, hold/toggle, call forwarding
- Call transfer via R key Quality of service2): ToS, Diffserv, configurable DSCP values for SIP and RTP

IP features and services Online directories

- Online directory and Yellow Page search (multiple directories supported) 2).
- Reverse search (number -> contact).
- Reverse lookup online (display of caller id from online directory)
- · Link tuser defined online directory

Email

- New Emails are indicated on the handset8) by illuminated MWI-key
- Read Emails on handset (up t560 characters) 2), 8)
- Delete Emails via handset2), 8).
- Support of POP3/POP3S Email accounts2), 8)

Applications and Services

- Easy access tonline information on handset8) via screensaver and interactive InfCenter: Weather, RSS Feeds, eBay Companion, Translator, Encyclopedia, Horoscope, Biorhythm, Unit Converter2), 8) User defined services2), 8)
- Initiate calls on handset from InfService pages (click-to-call) 2), 8)

Setup and provisioning

- Quickstart setup software
- Easy configuration via web server or from handset
- · Administrator friendly configuration via config file
- Plug and Play Auto-provisioning for retail variant via
- MAC address Auto-configuration code
- Plug and Play Auto-provisioning for operator/customer variant via:
- MAC address TR069, TR104, TR106, TR111 / part 1 (part 2 on request)

System and software

- Firmware update directly from handset, without file handling
- Firmware downgrade tfactory delivery status / last version
- DHCP client (Option 60, 114, 120)
- VLAN tagging
- HTTP Proxy support incl. 1.0 compatibility for chunked messages Increased virus protection thanks tprotected operating system
- Clock synchronization using NTP (Network Time Protocol) server

Please Enquire