

Grandstream GXP1450 HD IP Phone



Product Name: Grandstream GXP1450 HD IP Phone

Manufacturer: Grandstream

Model Number: GXP1450

Grandstream GXP1450 VoIP Phone

The Grandstream GXP1450 is a VoIP phone that features 2 SIP accounts, a 180x60 backlit graphical LCD screen, 3 XML programmable context-sensitive soft keys, dual network ports with integrated PoE, and 3-way conference. The GXP1450 is feature rich and comes at an affordable cost.

Grandstream GXP1450 Key Features

- 180 x 60 pixel backlit graphical LCD display with up to 4 level grayscale
- 2 dual color line keys (with 2 SIP accounts and up to 2 call appearances), 3 XML programmable context sensitive soft keys, 3-way conference
- HD wideband audio, superb full duplex hands free speakerphone with advanced acoustic echo cancellation and excellent double-talk performance
- Large phonebook (up to 500 contacts) and call history (up to 500 records)
- Automated personal information service (e.g. local weather, etc.), personalized music ring tone/ring back tone, flexible customisable screen content & format using XML and advanced Web and enterprise applications integration
- Dual switched auto sensing 10/100Mbps network ports with integrated PoE
- Automated provisioning using TR-069 or encrypted XML configuration file, SRTP and TLS for advanced security protection, 802.1x for media access control



Grandstream GXP1450 IP Phone Technical Specifications

Protocols and Standards

- SIP RFC2361
- TCP/IP/UDP
- RTP/RTCP
- HTTP/HTTPS
- ARP/RARP
- ICMP
- DNS (A record, SRV, NAPTR)
- DHCP
- PPPoE
- TELNET
- TFTP
- NTP
- STUN
- SIMPLE
- TR-069
- 802.1x

Network Interfaces

Grandstream GXP1450 HD IP Phone

- Dual switched 10/100Mbps ports with integrated PoE

Graphic Display

- Back-lit 180 x 60 graphical LCD display with up to 4 level grayscale

Feature Keys

- 2 line keys with dual-color LED and 2 independent SIP accounts
- 3 XML programmable context sensitive soft keys
- 5 navigation/menu/volume keys
- 10 dedicated function keys for: Hold, Speakerphone, Send/Redial, Transfer, Conference, Mute, Headset, Volume, Phonebook/Contacts, and Message (with LED indicator)

Voice Codec

- Support for G.723.1, G.729A/B, G.711u/a, G.726-32, G.722 (wide-band), iLBC, in-band and out-of-band DTMF (in audio, RFC2833, SIP INFO)

Telephony Features

- Hold
- Transfer
- Forward
- 3-way conference
- Call park
- Pickup
- Shared-call-appearance (SCA)/Bridged-line-appearance (BLA)
- Downloadable phone book (XML, LDAP, up to 2,000 items)
- Call waiting
- Call log (up to 2,000 records)
- XML customization of screen
- Off-hook auto dial
- Auto answer
- Click-to-dial
- Flexible dial plan
- Hot desking
- Personalized music ringtones and music on hold
- Server redundancy
- Fail-over

HD Audio

- Yes, both on handset and speakerphone

Headset Jack

- RJ9 and 2.5mm headset jack

Base Stand

- Yes, allow 2 angle positions

Wall Mountable

- Yes

QoS

- Layer 2 (802.1Q, 802.1p)
- Layer 3 (ToS, DiffServ, MPLS) QoS

Security

- User and administrator level passwords
- MD5 and MD5-session based authentication
- AES based secure configuration file
- SRTP
- TLS
- 802.1x media access control

Multi-language

- English, German, Italian, French, Spanish, Portuguese, Russian, Croatian, simplified and traditional Chinese, Korean, Japanese etc.

Upgrades and Provisioning

- Firmware upgrade via TFTP/HTTP/HTTPS
- Mass provisioning using TR-069 or encrypted XML configuration file

Power & Green Energy Efficiency

- Universal power adapter included: Input: 100-240VAC 50-60Hz; Output: +5VDC, 800mA
- Integrated Power-over-Ethernet (802.3af)
- Max power consumption 2.5W (power adapter)

Physical

- Unit dimension: 186mm (W) x 210mm (L) x 81mm (D)
- Unit weight: 0.8kg
- Package weight: 1.3kg

Temperature and Humidity

- 32-104°F / 0-40°C
- 10-90% (non-condensing)

Package Content

- Grandstream GXP1450 IP Phone
- Handset with cord
- Base stand
- Universal power supply
- Network cable
- Quick Start Guide

Compliance

Grandstream GXP1450 HD IP Phone

- FCC Part 15 (CFR 47) Class B
- EN55022 Class B
- EN55024
- EN61000-3-2
- EN61000-3-3
- EN 60950-1; AS/NZS CISPR 22 Class B
- AS/NZS CISPR 24
- RoHS
- UL 60950 (power adapter)

Price: £41.03

VoIPVN <http://voip.com.vn>