

Grandstream GXV3611_HD IP Camera



Product Name: Grandstream GXV3611_HD IP Camera

Manufacturer: Grandstream

Model Number: GXV3611-HD

GXV3611_HD Fixed Dome High Definition IP Camera

Grandstream's GXV3611 indoor fixed dome IP cameras provide an unobtrusive indoor solution that can be easily mounted on walls or ceilings for maximum surveillance protection. Ideal for advanced surveillance requiring razor sharp image clarity and archived video used for investigative purposes. Grandstream GXV3611_HD Key Features:

- Integrated microphone, speaker and smoke detector for maximum and out-of-the-box video + audio + smoke monitoring using industry standard SIP & VoIP technology
- Motion Detection and Alert Notification
- Integrated Power-over-Ethernet (802.3af)
- 24MB pre-/post-event recording buffer
- Easy installation and management using Grandstream's web-based graphical user interface

Grandstream's GXV3611_HD camera includes 2-Megapixel progressive scan CMOS sensor and advanced lens while delivering multi-rate H.264 real-time video streaming with a maximum resolution of 1,600 x 900 and at frame rate of up to 25fps. Using GSurf, Grandstream's free video management software, businesses can monitor and control up to 36 cameras simultaneously. Retail stores, restaurants, campuses, casinos, apartment buildings and business offices looking for a cost-effective, open standard surveillance solution can easily implement these two new indoor cameras for 24x7 security protection of people and assets. With SIP/VoIP support, business owners can also stream all monitoring activity to a mobile or video phone, from anywhere in the world, using the GXV3611's 2-way audio and video streaming capability.

Grandstream GXV3611_HD Technical Specification

Video

- Video Compression: H.264, JPEG, Motion, JPEG
- Pixel Dynamic Range: 71 dB, with SNRMAX 41dB
- Max Video Resolution: 1600 x 1200
- Max Frame Rate in Max Resolution: -20 fps for 1600 x 900 -25 fps for 1280 x 720 -30 fps for 800 x 450, 640 x 360, 480 x 270, 320 x 180 and 240 x 135
- Video Bit Rate: 32 Kbps - 4 Mbps, Adjustable (8 Mbps maximum)

Audio

- Audio Input: 3.5mm Line-In, built-in Microphone
- Audio Output: 3.5mm Line-out
- Audio Compression: G.711, G.726

Embedded Analytics

- Motion detection (up to 16 target areas).

Alarms

- Alarm Input: 1, Normal Open
- Alarm Output: 1, 125VAC/0.5A, 30VAC/2A

- Pre/Post-alarm Buffer: 24 MB

Security

- Video watermark, HTTPS, Password

Network

- Network Port: 10M/100M auto-sensing, RJ45
- Network Protocol: -TCP/UDP/IP -RTP/RTCP -RTSP -DCHP -PPPoE -DDNS -HTTP -HTTPS

Weight and Dimensions

- Weight: 0.43 Kg
- Dimensions: 138mm x 86mm (D x H)

Power Adaptor

- Output: 12VDC/1A
- Input: 100-240VAC, 50-60Hz

Please see the Brochure at the top of the page for more specifications.

Price: £92.86
