

Grandstream GXV3611_LL IP Camera



Product Name: Grandstream GXV3611_LL IP Camera

Manufacturer: Grandstream

Model Number: GXV3611-LL

Please Note: The Grandstream GXV3611_LL has been discontinued. For an alternative, we recommend taking a look at the Grandstream Fixed Dome IP Camera section.

GXV3611_LL Fixed Dome Low Light IP Camera

Grandstream's GXV3611 indoor fixed dome IP cameras provide an unobtrusive indoor solution that can be easily mounted on walls or ceilings for maximum surveillance protection. The GXV3611_LL captures and streams high quality real-time video under low light conditions (as low as 0.05Lux) and up to 30fps with full D1 (720x480) or VGA (640x480) resolution. It features multi-rate H.264 video compression with excellent image quality and can control up to 36 cameras using GSurf video management software. Grandstream GXV3611_LL Key Features:

- Integrated microphone, speaker and smoke detector for maximum and out-of-the-box video + audio + smoke monitoring using industry standard SIP & VoIP technology
- Motion Detection and Alert Notification
- Integrated Power-over-Ethernet (802.3af)
- 24MB pre-/post-event recording buffer
- Easy installation and management using Grandstream's web-based graphical user interface

Retail stores, restaurants, campuses, casinos, apartment buildings and business offices looking for a cost-effective, open standard surveillance solution can easily implement these two new indoor cameras for 24x7 security protection of people and assets. With SIP/VoIP support, business owners can also stream all monitoring activity to a mobile or video phone, from anywhere in the world, using the GXV3611's 2-way audio and video streaming capability.

Grandstream GXV3611_LL Technical Specification

Video

- Video Compression: H.264, JPEG, Motion, JPEG
- Pixel Dynamic Range: 71 dB, with SNRMAX 41dB
- Max Video Resolution: 1600 x 1200
- Max Frame Rate in Max Resolution: -20 fps for 1600 x 900 -25 fps for 1280 x 720 -30 fps for 800 x 450, 640 x 360, 480 x 270, 320 x 180 and 240 x 135
- Video Bit Rate: 32 Kbps - 4 Mbps, Adjustable (8 Mbps maximum)

Audio

- Audio Input: 3.5mm Line-In, built-in Microphone
- Audio Output: 3.5mm Line-out
- Audio Compression: G.711, G.726

Embeddded Analytics

- Motion detection (up to 16 target areas).

Alarms

- Alarm Input: 1, Normal Open

Grandstream GXV3611_LL IP Camera

- Alarm Output: 1, 125VAC/0.5A, 30VAC/2A
- Pre/Post-alarm Buffer: 24 MB

Security

- Video watermark, HTTPS, Password

Network

- Network Port: 10M/100M auto-sensing, RJ45
- Network Protocol: -TCP/UDP/IP -RTP/RTCP -RTSP -DCHP -PPPoE -DDNS -HTTP -HTTPS

Weight and Dimensions

- Weight: 0.43 Kg
- Dimensions: 138mm x 86mm (D x H)

Power Adaptor

- Output: 12VDC/1A
- Input: 100-240VAC, 50-60Hz

To see the whole specification please view our [datasheet](#).

Please Enquire
