

Grandstream GXV3662_FHD Fixed Dome IP66 Camera



Product Name: Grandstream GXV3662_FHD Fixed Dome IP66 Camera

Manufacturer: Grandstream

Model Number: GXV3662-FHD

Grandstream GXV3662_FHD Fixed Dome IP66 Camera

The Grandstream GXV3662_HD/FHD is a powerful, vandal-resistant and weather-proof dome IP camera of outstanding performance and quality. Its advanced ISP (Image Sensor Processor) is powered with state-of-the-art auto-exposure/auto-white-balance algorithm and a high quality lens. This helps to ensure high fidelity video quality that matches digital still camera color grade in a wide range of light environments.

Grandstream GXV3662_FHD Fixed Dome IP66 Camera Key Features

- High quality 1.2 Megapixels or 3.1 Megapixels CMOS sensor and lens
- Advanced multi-streaming rate real-time H.264, Motion JPEG at 720p resolutions
- Alarm input & output, audio input & output
- SD slot for local storage, 24MB pre/post event recording buffer
- Support Motion Detection and Notification on PC Client
- Built-in high performance streaming server to allow 10+ simultaneous viewers
- Embedded video analytics and SIP/VoIP support
- Support both variable bit rate and variable frame rate
- Integrated Power-over-Ethernet (802.3af)
- Full Onvif conformance with extensions in the near future

The GXV3662_FHD features cutting edge H.264 real-time video compression (720p HD) with excellent image clarity, industry leading SIP/VoIP for 2-way audio and video streaming to mobile phones and video phones, integrated PoE, IR-CUT switch for color or black & white operation mode, and advanced security protection. The GXV3662 can be managed with GSurf (Grandstream's intuitive FREE video management software that controls up to 36 cameras simultaneously) as well as other ONVIF compliant video management systems. It also offers an advanced and flexible HTTP API for easy integration with other monitoring systems. The Grandstream GXV3662 is a powerful network camera for professional surveillance application in outdoor environments.

Grandstream GXV3662_FHD Fixed Dome IP66 Camera - Technical Specifications

General

- Video Compression: H.264 MJPEG
- ONVIF Compliant: Yes
- Image Sensor: 1/3", 1.2 Megapixel CMOS, 128H x 960V
- Lens Type: 1/3", 3.3 ~ 12mm, F1.6 ~ F3.2, DC & Iris Manual Focus
- Sensitivity: 6.0V/Lux-sec (550nm)
- Max Frame Rate: 1,280 x 960 @ 30fps
- Video Bit Rate: 64 Kbps ~ 8 Mbps, multi & rate for preview & recording
- Audio Input / Output: Line & In, Line - Out
- Alarm Input / Output: Input: Vin ≤ 45V / Output: 125VAC/0.5A, 30VDC/2A, normal open
- Audio Compression: G.711 a/u
- Pre- Post Alarm Buffer: 24MB
- Security: Video Watermark (pending), HTTPS, Password
- Network Port: 10M/100M auto sensing, RJ45 with integrated PoE
- Multi & streaming - rate: Yes
- SIP/VoIP Support: Yes
- Dimensions (L x W x H): 153mm (D) x 115mm (H)
- Weight: 1.19kg
- Power: Output: 12VDC/1A; Input: 100 ~ 240VAC, 50 & 60Hz

Price: £264.30

VoIPVN <http://voip.com.vn>