

Grandstream GXW4224 FXS Analog VoIP Gateway



Product Name: Grandstream GXW4224 FXS Analog VoIP Gateway

Manufacturer: Grandstream

Model Number: GXW4224

Grandstream GXW4224 FXS Analog VoIP Gateway

The Grandstream GXW4224 is a next generation, high performance analog VoIP gateway that is fully compliant with SIP standard and interoperable with VoIP systems, analog PBX and phones on the the market. The GXW4224 features 24 FXS analog telephone ports and with rich telephony functionalities, superb voice quality, easy provisioning, flexible dialing plans, advanced security protection, the GXW4224 has a lot to offer.

Grandstream GXW4224 FXS Analog VoIP Gateway Key Features

- 24 telephone FXS ports with both RJ11 and 50-pin Telco connectors, as well as per port LED
- Gigabit Ethernet and a backlit 128x32 graphic display with support for multiple languages
- 2/3/4 SIP Server profiles per system and independent SIP account per port
- Supported voice/Fax codecs include G.711, G.723.1, G.726A/B, iLBC, T.38 Fax
- Advanced carrier grade 128ms-tail-length G.168 line echo cancellation
- Over-voltage and over-current protection(ITU-T, K.21)
- Support VMWI, NEON LED and stutter tone for message waiting indication
- Automated provisioning using TR-069 or AES encrypted XML configuration file; TLS/SRTP/HTTPS for advanced security and privacy protection

The GXW4224 offers both small and medium businesses a cost-effective hybrid IP and analog telephone system that allows them to enjoy the benefits of VoIP communications while preserving investment on existing analog phones, Fax machines and legacy PBX systems.

Grandstream GXW4224 FXS Analog VoIP Gateway - Technical Specifications

General

- Telephone Interfaces 24 x RJ11 FXS ports plus 1/1/2 x 50 pin Telco connectors
- Network Interfaces 1 x 10M/100M/1000Mbps auto-sensing RJ45 port
- Audio Codecs G.711, G. 723, G.726 (40/32/24/16), G.729A/B/E, iLBC
- LED Indicators LAN Link, LAN Activity, Per Telephone port
- LCD Display Backlit 128x32 graphic LCD display with support for multiple languages
- Voice-over-Pack Capabilities G.168 carrier grade line echo cancellation, dynamic jitter buffer, modem detection & auto-switch to G.711
- Voice Compression G.711, G.723, G.726, G.729 A/B, iLBC
- Fax over IP T.38 compliant Group 3 Fax Relay up to 14.4kbps and auto-switch to G.711 for Fax Pass-through, Fax Datapump V.17, V.21, V27ter, V29 for T.38 fax relay
- Telephony Features Caller ID display or block, call waiting, blind or attended transfer, call forward, do not disturb, 3-way conference, last call return, paging, message waiting indicator LED (NEON LED) support and stutter tone, auto dial, flexible dial plan
- QoS DiffServ, TOS, 802.1P/Q VLAN tagging
- Network Protocols TCP/UDP, RTP/RTCP, HTTP/HTTPS, ARP, ICMP, DNS, DHCP, NTP, TFTP, PPPoE, STUN, LLDP
- DTMF Method Flexible DTMF transmission methods including In-audio, RFC2833, and /or SIP INFO
- Singaling SIP (RFC 3261) over UDP/TCP/TLS
- SIP Server Profiles & Accounts Per System 2/3/4 distinct SIP server profiles per system and independent SIP account per telephone port
- Provisioning TFTP, HTTP, HTTPS, TR069

Price: £357.89

VoIPVN <http://voip.com.vn>