

# Mitel (Aastra) 6737i IP Phone (37i)



Product Name: Mitel (Aastra) 6737i IP Phone (37i)

Manufacturer: Mitel Aastra

Model Number: AAST-6737I

## Mitel (Aastra) 6737i IP Phone

The Mitel (Aastra) 6737i is a high-level phone designed for users who have high demands from both their VoIP phones and their networks. The 6737i IP Phone can provide impressive voice quality through the use of wideband audio and offers support for today's high speed network through dual Gigabit Ethernet ports.

### Mitel (Aastra) 6737i Key Features

- Up to 9 lines with call appearances
- Multi-proxy support
- Distinctive ringing and priority alerting
- XML support for productivity-enhancing applications
- Supports Power over Ethernet (PoE)
- Call forward/Call transfer/Call waiting/Call timer
- Callers log
- Local 3-way Conference
- Programmable speed dial
- Missed call notification
- Busy Lamp Field (BLF)
- Supports up to 3 M670i (536M) or M675i (560M) expansion keypads

With exceptional voice quality and value, the 6737i is an advanced featured and expandable IP Telephone. The phone has a large 144 x 128 pixel graphical backlit LCD display, featuring 12 programmable softkeys that can offer up to 30 different functions, and supporting up to 9 simultaneous calls.

### Remarkable Audio

The 6737i IP Phone incorporates Aastra Hi-Q&trade; audio technology to deliver enhanced performance and voice clarity. Integrating wideband audio software and hardware, the Aastra 6737i IP Phone maximizes the acoustic performance to deliver a remarkable audio experience on every call, whether using the handset, handsfree speakerphone or headset port.

### XML Browser

The Aastra IP Phone is equipped with XML browser capabilities and an extra large display with dynamic softkeys to easily access customized services and applications. This feature provides unlimited potential to customize the Aastra 6737i IP Phone to meet your specific business needs or vertical applications using the display and keypad.

### Enhanced Call Management

The Aastra 6737i IP Phone includes features such as shared call and bridged line appearances, call forward, call transfer, call waiting and 3-way conference providing enhanced call flexibility and control.

### Expandability

The Aastra 6737i IP Phone offers two different module extension options. It supports up to three Aastra M670i modules, each offering 36 keys with LED indicators to create a feature rich attendant console. Or, it will also support up to three of the advanced Aastra M675i modules, each offering 60 keys with a screen based LCD display and LED system.

### Simplified Deployment

The Aastra family of IP telephones are designed to save your business time and money. Dual auto-sensing Gigabit switch Ethernet ports eliminate additional wiring and simplify installations. Integrated IEEE 802.3af Power-over-Ethernet allows easy deployment with centralized powering and backup.

# Mitel (Aastra) 6737i IP Phone (37i)

Note: Please refer to the Aastra IP Phone Range Detailed Comparison Table for more information.



## Mitel (Aastra) 6737i IP Phone Technical Specifications Feature Keys

- Up to 9 lines with call appearances
- 4 line/call appearance buttons with LEDs
- 4 navigational keys
- 12 customizable softkeys with LEDs, programmable up to 30 functions
- 8 dedicated hard keys including Hold, Redial, Speakerphone/Headset toggle, Mute, Options, Goodbye, 2 volume keys

## Audio and Codecs

- Aastra Hi-Q Audio Technology
- Hearing aid compatible (HAC) handset
- Full-duplex quality speakerphone
- Codecs: G.711  $\mu$ -law / A-law, G.729, G.722 wideband, BV16, BV32, L16
- Independent volume setting for handset/speaker/headset
- Echo cancellation
- Comfort noise
- Packet loss concealment
- Modular Headset Connector with built-in amplifier
- Electronic Hookswitch (EHS) support for wireless headsets
- Voice Quality Metrics, including MOS

## Display and Indicator

- 144x128 pixels graphical backlit LCD display
- Soft white backlight for user comfort in any lighting environment
- Backlight Auto-on setting with configurable timer (power saving)
- LED for call and message waiting indication

## Security

- User and administrator level passwords for login
- Encryption of configuration files
- HTTPS configuration download and web management
- Phone lock with PIN
- Digest Authentication
- Transport layer Security (TLS)
- Secure Real-Time Protocol (SRTP)

## XML API Capabilities

- Display control based on user actions or on events

# Mitel (Aastra) 6737i IP Phone (37i)

- Dynamic Phone Configuration
- RTP Streaming control
- CTI applications
- See XML API Documentation for more details

## Expansion Modules

- Supports up to 3 M670i or M675i modules

## Localization

- Multi-lingual support &ndash; English, French, Spanish, Italian, German; Downloadable language pack support for customization and additional language translations
- Country-specific call progress tones and cadences
- Latin1, Latin 2 Character set Protocol
- IETF SIP (RFC3261) and associated RFCs Networking and Provisioning
- Dual 10/100/1000 Mbps switch Ethernet ports
- Manual or Dynamic Host Configuration Protocol (DHCP) IP address setup
- Support of multiple DHCP options: 66, 60, 43, 77, 159, 160
- Time and date synchronization using SNTP
- Quality of Service (QOS) support &ndash; IEEE 802.1 p/Q VLAN and priority tagging, Type of Services (TOS), and Differentiated Services Code Point
- Network Address Translation (NAT), STUN, TURN support
- Integrated HTTP/HTTPS server for web administration and maintenance including a built-in troubleshooting section
- Mass deployment via central provisioning of user configuration files &ndash; TFTP, FTP, HTTP, HTTPS
- Redundant server support &gt;&gt; DNS-SRV &gt;&gt; Local backup registrar and/or proxy server
- RTCP support (RFC1889)
- RTP streaming for Paging and Intercom applications
- IEEE 802.1x
- LLDP-MED

## Power

- Integrated IEEE 802.3af Power Over Ethernet (PoE) support
- AC adapter (48V DC) sold separately. AC adapter is required if using more than 1 expansion module

## Package Contents

- Aastra 6737i IP Phone phone
- Handset and coil cord
- 2 x Footstand
- Ethernet cable
- Wall mounting kit
- Installation Guide

## Physical

- 23.5 cm W x 20.8 cm D x 8.0 cm H (9.3&rdquo;W x 8.2&rdquo;D x 3.2&rdquo;H)
- 940 g (33.0 oz)
- 4 position footstand
- Wall mountable

# Mitel (Aastra) 6737i IP Phone (37i)

## Operating Conditions

- Temperature: 0&deg;C to 50&deg;C (32&deg;F to 122&deg;F)
- Relative Humidity: 20% to 90%, noncondensing
- Storage Temperature: -50&deg;C to 70&deg;C (-58&deg;F to 158&deg;F)

## Europe/CE Certifications

- ROHS compliant
- WEEE (2002/96/EC)
- CE Mark (89/336/EEC EMC Directive and 73/23/EEC Low Voltage Directive)

## EMC Certifications

- FCC Part 15 Class B
- ICES-003 Class B
- AS/NZS 3548 Class B
- EN55022 Class B
- CISPR22 Class B
- EN55024
- EN61000 4-2, 4-3, 4-4, 4-5, 4-6, 4-8, 4-11

## Safety Certifications

- CAN/CSA C22.2 No. 60950
- EN 60950
- UL 60950-1

## Telecom Certifications

- FCC Part 68 (Hearing Aid Compatibility)
- AS/ACIF S004

**Price: £139.50**

---