

OpenVox A400P30 - 3 FXS



Product Name: OpenVox A400P30 - 3 FXS

Manufacturer: OpenVox

Model Number: A400P30

OpenVox A400P30 - 3 FXS

The OpenVox A400P30 - 3 FXS is an OpenVox A400P bundled with 3 FXS modules.

You can also add FXO-100 or FXS-100 modules to use with this product according to your requirements.

OpenVox A400P is designed to be fully compatible with the TDM400P Asterisk Analog Telephony card.

The A400P supports up to a total of 4 FXO and/or FXS connections with FXO-100 and/or FXS-100 modules.

The FXO-100 (FXO) module allows the A400P card to terminate analog telephone lines (POTS).

The FXS-100 (FXS) module allows the A400P card to terminate analog telephones.

Key Features and benefits:

- Scalable: Just add additional cards to extend the system.
- Easy to use: Full software and hardware compatible with TDM400P.
- Modular design: Can upgrade at any time by adding extra FXO or FXS modules up to a total of 4 per card. (A400P30 comes with three FXS modules.)
- Both 3.3v or 5v PCI slots can be used with this card.
- Module Pin to Pin compatible with X100M and S100M. You can use X100M/S100M modules on this card, or use FXO-100/ FXS-100 Modules from OpenVox.
- Excellent value: High quality at a low price.
- Application ready: Use Asterisk to build your IP-PBX system.
- RoHS Compliant.
- Certificates: CE, FCC
- Five year warranty

Technical Specifications

- Up to 4 ports through a combination of FXS and FXO modules
- 4 RJ-11 interfaces on a single PCI bracket
- 32 bit 33MHz PCI and fully PCI 2.2 compliant
- 32 bit bus master DMA data exchanges across PCI interface at 132 Mbytes/sec
- Autosense compatibility with 5 V and 3.3 V PCI busses compatible
- Firmware accelerate I/O access to achieve high stability

Power

- 2.77W Minimum, 11.6W Maximum at 3.3 V or 5 V.

Operation temperature

- 0°C to 50°C

Storage temperature

- -40°C to 125°C

Dimension

- 136.3mm*101mm*16mm

OpenVox A400P30 - 3 FXS

Weight

- 82g

Price: £93.80

VoIPVN <http://voip.com.vn>