

Product Name: Openvox V100-BOX-128 (Up to 128 transcoding Sessions)

Manufacturer: OpenVox

Model Number: V100-BOX-128

Openvox V100-BOX Up to 128 transcoding Sessions, Enclosure V100-BOX-128 The Openvox V100-BOX-128 is an integrated box designed to streamline installation, With an extern Power Supply, it can work alone by using Ethernet port and also being stacked up to 5 instances on a 19 inch rack mount. The V100-BOX from Openvox can be worked with Asterisk® and FreeSWITCH®.

Feature

- High density up to 128 transcoding Sessions
- No addionnal License Fee1
- Relieve Host CPU Load
- Release API for Integration
- OS: Linux and Windows
- Integrates in Asterisk® and FreeSWITCH®
- Support distributed or intergrated Application

Openvox V100-BOX-128 - Technical Specifications Codec Support

• G.711 • GSM-FR

• G.722 • GSM-EFR

• G.722.1 • AMR

• G.726

• AMR-WB (G.722.2)

• G.729AB • iLBC

- * Except for AMR and AMR-WB Target Applications
- Hosted VoIP GateWay
- Conferencing Server
- IVR Server
- Distributed Office PBX
- Call Centers

Dimensions

• 131x67.5x31mm

Interface

• 10/100/1000 BASE-T RJ45

Power Requirments

• 0.6A @12V

Operating Temperature Range

• 0 – 50 °C

Humidity

• 10 TO 90% NON-CONDENSING

Hardware And Software Requirement

• Windows/Linux in Host

Certifications

• FCC Part 15B,EN55022 Class B,EN55024 EN60950 (Pending)

Warranty

• 5-year warranty

Related Accessories



The OpenVox V100-Bracket is a 1U & Damp; 19" bracket, designed for rackmounting installation of up to 5 instances of V100-BOX.

Price: £546.40