

Patton SmartNode SN4970/4E15VR/EUI 4 Port T1/E1 PRI 15 VoIP Channels VoIP Gateway



Product Name: Patton SmartNode SN4970/4E15VR/EUI 4 Port T1/E1 PRI 15 VoIP Channels VoIP Gateway

Manufacturer: Patton Inalp

Model Number: SN4970/4E15VR/EUI

Patton SmartNode SN4970/4E15VR/EUI 4 Port T1/E1 PRI 15 VoIP Channels VoIP Gateway
Patton SmartNode 4 T1/E1 PRI VoIP Gateway, 1x GigEthernet, 15 VoIP channels; upgradeable to 60, Failover Relay, External UI Power, IPv6 ready. The Patton SmartNode 4970 15 VoIP Channels 4 Port T1/E1 PRI Failover Relay VoIP Gateway supports every industry-standard CODEC to deliver tollquality voice on every call. The Patton SmartNode 4970 30 VoIP Channels 1 T1/E1 PRI VoIP Gatewaycan also be upgraded to 30 calls and is a Hi-Capacity, 1 GigEthernet,External UI power Voip Gateway.

Patton SmartNode 4970 15 VoIP Channels 4 Port T1/E1 PRI Failover Relay VoIP Gateway Features

- 15 VoIP Channels —with up to four T1/E1/PRI ports and a single Gigabit Ethernet port.
- Upgradeable to 60 VoIP Channels
- Proven Interoperability—SIP interop with major IP PBX, Softswitch and VoIP Service Providers. Over 100,000 SmartNode deployments worldwide. ISDN/PSTN compliance in nearly every country.
- Transparent Telephony Features—Complex number manipulation and mapping for seamless integration with existing infrastructures, CLIP, CLIR, hold, transfer and much more.
- Flexible Mounting Options—The device can be placed on a desktop or installed in a 19-inch rack using the optional rack ear kit (INS-KIT-RACKEARS-11/19)

The Patton SmartNode 4970 15 VoIP Channels 4 Port T1/E1 PRI Failover Relay VoIP Gateway model offers Failover Relay which is PSTN fallback to ensure business continuity in case of a power outage. All SN4970 models include Patton's SIP Survivability Suite which includes PSTN Fallback in the event of a network outage, SIP registrar allowing SIP clients to continue to make calls in the event of a network outage, and dial backup enabling dial-up connection to the PSTN during network and power outages.

Patton SmartNode 4970 15 VoIP Channels 4 Port T1/E1 PRI Failover Relay VoIP Gateway offers a smooth transition to VoIP with strong number portability. This allows you to continue to make and receive calls via the PSTN while your SIP provider is in the sometimes long process of porting your numbers over to SIP. When your numbers are completely SIP based, the SN4970 will dynamically switch to SIP so the transition from POTS to VOIP is seamless and instant.

Patton SmartNode 4970 15 VoIP Channels 4 Port T1/E1 PRI Failover Relay VoIP Gateway
Specifications:

PSTN:

- Up to four T1/E1/PRI ports (NE/TE)
- Signaling support (ISDN DSS-1, NI-2, Q.SIG, CAS Robbed bit loop and ground start, E&M, immediate, wink, double wink)
- ISDN AOC/ECT
- ISDN speech, audio & data (Fax Gr 4, UDI 64, RDI64)
- ISDN supplementary services
- CAS protocols: RBS (Loop start, ground start, E&M wink, intermediate, double-wink) and R2/MFC-R2 (Q.400–Q.490 and Configurable country profiles), fallback-relays on 4 port versions

Patton SmartNode SN4970/4E15VR/EUI 4 Port T1/E1 PRI 15 VoIP Channels VoIP Gateway

VoIP:

- SIPv2 (SIP Info, Update, PRACK, Privacy, Refer), B2BUA, H.323v4 (H.235, Early H.245, H.245 tunneling, fast-connect)

Voice Processing:

- Codec G.711 a-law/mu-law, G.723, G.729ab, G.726, G727, T.38 fax relay (9.6 k, 14.4 k)
- G.711 transparent fax and bypass
- 128 ms echo cancellation

Call Routing and Services:

- Regular expression call routing and manipulation
- number blocking
- short-dialing
- digit collection, distribution and hunt groups

Data Interfaces:

- One 10/100/1000 TX Ethernet Port
- Autosensing
- Auto-MDI
- Full-duplex

Management:

- Web/HTTP, CLI with local console & remote Telnet access
- HTTP/TFTP configuration & firmware loading
- SNMP MIB II and product MIB
- SYSLOG
- Secure autoprovisioning for both firmware & unit/subscriber configuration
- Built-in diagnostic tools (trace, debug, call generator)

Power:

- Internal Power: 100~240VAC (50/60 Hz)

Price: £1,448.40
