Polycom CX300 IP Phone Microsoft Lync (OCS)



Product Name: Polycom CX300 IP Phone Microsoft Lync (OCS)

Manufacturer: Polycom Model Number: CX 300

Polycom CX300 IP Phone Microsoft Lync (OCS)

The Polycom CX300 brings a new meaning to the USB desktop phone with a two-line monochrome display, telephone keypad and wideband high fidelity audio. The Polycom CX300 IP Phone seamlessly integrates with Microsoft Office Communications Server 2007 R2 with the design of a regular handset includeing convenient buttons for controlling calls, The CX300 is a full featured USB desktop phone optimized for use with Microsoft Office Communications Server 2007 R2 with the look, sound and feel of a conventional enterprise-grade telephone with plug-and-play ease of use.

Polycom CX300 Key Features

- Superb voice quality Clear high definition wideband audio maximizes the accuracy and productivity of real-time conversations whether in handset, full duplex speakerphone, or headset mode.
- Ease of provisioning Seamless integration with and complement to the capabilities of Microsoft Office Communicator 2007 R2.
- Enhanced presence indicator Presence status monitoring to efficiently route calls.
- Familiar form factor Convenient dial pad and display like a traditional phone.
- Ease of Use Driverless plug-and-play USB operation from phone to PC.
- Unique Collaboration Polycom offers the only complete line of integrated voice and visual communication solutions for Microsoft collaboration tools.

Traditional Form Factor

The Polycom CX300 was designed to be used as a regular handset. Calls may be placed or answered using the phone or a Microsoft Office Communicator 2007 R2 client window. Like a traditional phone, the Polycom CX300 IP Phone includes convenient buttons for controlling calls. The Polycom CX300 IP Phone also includes advanced features such as a presence status indicator and integrated message waiting indicator.

Superior Voice Quality

The Polycom CX300 IP Phone delivers remarkable high definition audio quality for the ultimate voice communications experience. With its sleek, high-quality handset and its full duplex, hands-free speakerphone, the Polycom CX300 IP Phone enables crystal-clear, natural conversations without echoes or feedback.

Easy to Deploy and Use

The Polycom CX300 IP Phone connects and powers through an integrated USB cable for easy installation and use, so there are no extra cables to carry and no drivers to install. The Polycom CX300 is optimized for Office Communicator 2007 R2 and is compatible with Microsoft Windows XP or Microsoft Windows Vista operating systems.

Polycom and Microsoft Solutions

Polycom CX300 IP Phone Technical Specifications Device Controls and Keypad

Polycom CX300 IP Phone Microsoft Lync (OCS)

- 4x3 Dialpad
- Redial key
- Flash Key
- Delete Key
- Mute/un-mute key
- Speaker on/off key
- Handset/headset key
- Volume up/down key

LED Indicators

- Off hook indicator
- · Voice messaging indicator
- Speakerphone indicator
- Headset indicator
- Call forwarding indicator
- Multi-color LED presence indicator

Audio

- TIA-920
- Frequency response: 200 7kHz
- >58dB [200, 7000] Hz
- Dynamic range: >80 dB (@ 1kHz)
- Total Harmonic Distortion + Noise: <3% (@ 200 7kHZ)

Auxiliary Audio Output

• RJ-22 headset jack with built-in amplifier

Audio Enhancements

- Automatic Gain Control
- Dynamic Noise Reduction
- Acoustic Echo Cancellation

Minimum System Requirements

- Microsoft Windows XP or Windows Vista
- PC with Office Communicator 2007 R2 version 3.5.6907.37 or a later version installed
- One available USB 2.0 compliant connection

Power

- Supply voltage 5V provided by USB connection
- Power consumption 500 mA

Device to PC Interface

- USB 2.0
- Captive 6.56 feet (2.0 m) USB cable

- Handset: 19.05 x 5.08 x 1.91 cm (7.5 x 2.0 x 0.75 in)
- Cradle: 8.89 x 13.97 x 12.7 cm (3.5 x 5.5 x 5.0 in)

Weight

- Unit: 1.10 kgs (2.43 lbs)
- Handset: 0.21 kgs (0.45 lbs)
- Shipping Weight: 1.10 kgs (2.43 lbs)

Environmental Requirements

- Temperature: 0°C to 40°C (32°F to 104°F)
- Relative Humidity: 95% max (non-condensing)
- Altitude: -304.8 meter to 3962.4 meter (-1000 feet to 13,000 feet)
- Light Exposure: Fluorescent overhead lighting and window filtered daylight (typical offices)

Polycom CX300 IP Phone Ships With:

- Polycom CX300 IP Phone base
- Handset
- 6 ft. handset curly cord
- Captive USB cable
- Quickstart Guide
- Product Registration Card
- Warranty card

Regulatory Compliance

- Electrical Safety: UL60950-1 (USA / Canada), IEC / EN60950-1 (EU), GOST, MIC, CQC
- EMC General: CISPR22
- EMC USA (Class B): FCC Part 15
- EMC Canada (Class B): ICES00.3: 1998
- EMC EU (Class B): EN 55022, EN 55024
- EMC ROW (Class B): C-Tick (Australia), VCCI (Japan), GOST (Russia), MIC (Korea), CQC (China)

Price: £89.80