

Polycom CX600 IP Phone Microsoft Lync (OCS)



Product Name: Polycom CX600 IP Phone Microsoft Lync (OCS)

Manufacturer: Polycom

Model Number: CX 600

Polycom CX600 IP Phone Microsoft Lync (OCS)

The Polycom CX600 is a full-featured UC desktop phone that is optimized for use with Lync Server 2010 environments. This helps office and cubicle workers maximize productivity.

Polycom CX600 Key Features

- Revolutionary voice quality & Polycom HD Voice technology in the handset, headset, and speakerphone for stunning voice quality and clarity.
- Standalone IP phone for use with Lync Server software & Embedded client does not require a PC to make calls, gain access to personal contact information, call logs, calendar information or other advanced features.
- Enhanced presence indicator & On-screen presence status indicators for each of a user's contacts and a large, bright LED shows your current presence state.
- Gigabit Ethernet support & Future proofs network infrastructure investment.
- Unique collaboration & Polycom offers the only complete line of integrated voice and visual communications solutions for Microsoft collaboration tools.

The Polycom CX600 delivers all the features included in Lync Server 2010 environments to provide a cost effective, mainstream desktop phone. The phone features Polycom HD Voice technology for crystal-clear calls.

Native Lync 2010 Phone Edition software delivers a rich user interface for placing, receiving, and managing calls. The large 3.5-inch high resolution color display and easy navigation buttons enable familiar dialing controls, calendar and contact directory access, and presence indication. The Polycom CX600 IP Phone also features a USB port to enable optional, "Better Together" capabilities when used in conjunction with a PC.

Seamless integration with Lync Server enhances user experience and provides easy setup and configuration. Built-in dual Gigabit Power over Ethernet (PoE) ports provides full high speed data connectivity between the network and a user's computer, to enable bandwidthintensive applications on the user's desktop.

Polycom CX600 IP Phone Technical Specifications

Audio - General

- Polycom HD Voice technology (Polycom Acoustic Clarity technology, mechanical design and wideband codec support)
- Individual volume settings with visual feedback for each audio path
- Voice activity detection
- Comfort noise fill
- DTMF tone generation/DTMF event RTP payload
- Low-delay audio packet transmission
- Adaptive jitter buffers
- Packet loss concealment

- Background noise suppression
- Cellular Phone Immunity
- Automatic gain control
- Dynamic noise reduction
- Acoustic echo cancellation

Audio - Handset

- Handset Frequency response: 150 – 7kHz
- Compliant with ADA Section 508 Recommendations: Subpart B 1194.23 (all)
- Hearing aid compatible (HAC) for magnetic coupling to approved HAC hearing aids

Audio - Headset Port

- Dedicated RJ-9 headset port
- Headset port frequency response: 150 – 7kHz

Audio - Speakerphone

- Full Duplex speakerphone, compliant with IEEE 1329 Type 1
- Acoustic Echo Cancellation
- Speaker frequency response, 200 – 7kHz
- Speaker volume, maximum at 1/2 meter peak volume: 81dB
- Mic frequency response: 150 – 7kHz
- Mic pickup: 2.5m (8 ft.)

CODEC support

- Microsoft RTAudio
- G.722.1
- G.711 (narrowband, A-law and μ -law)

User Interface

- Display, 3.5", QVGA TFT 24-bit color graphical display, 320 x 240 pixels, with Unicode character capability
- LED backlight with adjustable brightness
- Backlight auto-dim when not in use

Accessibility

- High contrast UI graphic screen option (software)
- TTY compatible headset port
- Compatible with commercially-available TTY adapter equipment
- TTY compatible handset port

Buttons/Keys

- 12-button dial pad, 0 - 9, *, #
- Volume Up & Volume Down
- 2-way navigation: Up, Down, Select
- Home, Previous
- 2 soft keys + Menu
- Hookswitch for handset
- Mute/unmute

Polycom CX600 IP Phone Microsoft Lync (OCS)

- Speakerphone
- Headset

Indicators, LED

- Ringing/In Call/Hold
- Speaker
- Mute
- Headset
- Voice Mail
- Presence Indicator

Connectivity

- Ethernet switch 2-port Gigabit Ethernet switch 10/100/1000 Base-T with RJ45 connector ports
- IEEE 802.3af Gigabit Ethernet 10/100/1000 Base-T
- USB Device port, Type B female
- USB Host port, Type A female (disabled, for future use)
- Headset port, RJ9
- Handset port, RJ9

User Interface Languages

- English, French, Spanish, German, Italian, Dutch, Russian, Brazilian Portuguese, Japanese, Korean, Simplified Chinese, Traditional Chinese, Finnish, Swedish, Norwegian, Danish

Software Features

- Pre-requisites: Microsoft Lync Server 2010, Microsoft Lync 2010
- Basic Mode: Contacts, Photos, Message waiting indicator, Standard Enterprise IP-PBX features, CAC, Survivability, E911 (US only), call park, etc., Teleworker support, Conference leader experience
- Enhanced Mode: Individual Voice Mail listings, Calendar, Join Conference, "Better Together", Lync integration call logs

Power

- Built-in, auto-sensing IEEE 802.3af-2003 Power over Ethernet Class 2
- Optional AC power kit

Physical

- Weight (phone with handset): 993g
- Dimensions (d x w x h): 191 x 241 x 191 mm;
- Security cable lock slot

Operating Conditions

- Temperature: 0 to +40 degrees C (+32 to 104 degrees F)
- Relative Humidity: +10% to 90%, non-condensing
- Storage Temperature: -40 to +85 degrees C (-40 to +185 degrees F)

Polycom CX600 Ships With

- Polycom CX600 IP Phone Base

Polycom CX600 IP Phone Microsoft Lync (OCS)

- 3 position stand
- Handset
- 6 ft. handset curly cord
- Captive USB cable
- Quickstart Guide
- Warranty Card

Included Accessories

- Ethernet cable, 7 ft (2m)
- USB Cable, A & B (for "Better Together"), with B-type connector, 7 ft (2m)
- 3-Position stand for tilt adjustment

Accessories (available separately)

- AC Power Kit, 5-pack, with 24V PSU and 2m line cord with local plug
- Wall Mount Kit: bracket with ~100mm Ethernet patch cord

Regulatory Certifications

- EMC & General: CISPR22
- EMC & USA (Class B): FCC Part 15
- EMC - Canada (Class B): ICES00.3: 1998
- EMC & EU (Class B): EN 55022, EN 55024
- EMC & ROW (Class B): C & A Tick (Australia), VCCI (Japan), GOST (Russia), KCC (Korea), TRA (UAE), Telepermit PTC220 (New Zealand)

Electrical Safety Certifications

- UL60950-1 (USA / Canada)
- IEC / EN60950-1 (EU)
- GOST(Russia)
- KCC(Korea)

Price: £201.60
