

# Polycom CX8000 Panoramic Video Conferencing Station



Product Name: Polycom CX8000 Panoramic Video Conferencing Station

Manufacturer: Polycom

Model Number: CX 8000

## Polycom CX8000 Panoramic Video Conferencing Station

The Polycom CX8000 for Microsoft Lync is an ideal solution for any organization that has deployed Microsoft Lync to seamlessly connect and collaborate among individuals and groups of people regardless of location. The Polycom CX8000 solution combines powerful software features of Microsoft Lync for effective interactive collaboration, and industry-leading audio, video, and control solutions that are designed to enhance the conference room experience, resulting in more productive meetings.

### Polycom CX8000 Key Features

- Deployment options - Traditional front-of-room camera - Center of table camera
- Single or dual monitor support - Ready for addition of one or two touch-capable main monitors
- Crestron-ready - Integrates with the complete line of Crestron automation solutions, controlled from the CX8000 tabletop controller

### Polycom CX8000 Technical Specifications

#### Benefits

- Easy to use—Intuitive touch screen technology and simple Lync-based user interface makes it easy to operate with little training
- Enhanced group collaboration—Share, annotate, and edit content with your partners and clients from remote sites
- Market leading tabletop display—Designed to seamlessly integrate with Crestron room control solution
- Cost effective—Leverage existing Polycom infrastructure and whiteboards you own. With no dedicated PC needed, installation is easy and sets up in minutes
- Flexible deployment option—The system works in on-premises Lync Server 2013, Office 365, or hybrid environments

#### Kit contents

The Polycom CX8000 FOR kit ships with:

- Crestron UC Codec for Microsoft®; Lync®;
- 10" Tabletop Touch Screen Controller
- Wall Mount Kit for 65" Touch Display2
- Sound bar
- HD camera with built-in microphone
- Cables and accessories

#### Extended Wiring Interface (2Wire/UTP)

- Cable Type 2Wire, Cat 5e., Cat 6. or Similar
- Impedance 25? to 100?
- Transmit Coverage Max.720ft.(220M)@Cat6.

The Polycom CX8000 360 kit ships with:

- All components in the CX8000 FOR kit
- CX5100 Unified Conferencing Station Connections
- Network: 10Base-T/100Base TX/1000Base-T Ethernet with 14 ft (4.3 m) CAT6 cable included

# Polycom CX8000 Panoramic Video Conferencing Station

## Power

- Overall system rating (exclusive of monitors, CX5100): 120-240 VAC, 50/60 Hz 3.0A
- Sound Bar: 0.3A Max; 25w per stereo channel
- PoE module: 0.5A, 13BTU/hr @ 240 VAC
- Codec: 1.25A, 287 BTU/hr

## Wall mount

- Mounts to wall or mobile cart (available separately) -12°; tilt adjustment
- Built in lateral shift
- 160 lb (72 kg) weight capacity Tabletop touch screen
- Dimensions: 4.76" H x 10.13" W x 5.85" D (121 x 258 x 149 mm)
- Cable Length: 25 ft (7.62 m)
- Color: Black

## Tabletop touch screen

- Dimensions: 4.76" H x 10.13" W x 5.85" D (121 x 258 x 149 mm)
- Cable Length: 25 ft (7.62 m)
- Color: Black

## Environmental requirements

- Operating & Non-operating - Temperature: 5 to 40°C - Relative humidity: 15 to 85% (non-condensing)

## Regulatory compliance

- Safety - 2006/95/EC low voltage directive - UL 60950-1/EN 60950-1 - CSA C22.2 60950-1/IEC 60950-1 - AS/NZS 60950-1
- EMC - 2004/108/EC EMC directive - CISPR 22 (ICES, AS/NZS) - FCC 47CFR Part 15 - EN 55022/EN 55024
- Environmental - 2011/65/EC RoHS directive

**Price: £9,494.00**

---