

Sangoma A500 BRI Module



Product Name: Sangoma A500 BRI Module

Manufacturer: Sangoma

Model Number: A500MODULE

A500 BRI ISDN PCI / PCI Express Card (A500MODULE)

The Sangoma A500 S/T BRI Interface Card delivers superior audio quality and scalability. Expand from two to twenty-four ports of BRI with optional Octasic[®]; Telco-grade, hardware echo cancellation.

A single PCI or PCI Express slot hosts the connection for up to 24 ports and ensures common synchronous clocking for all channels with no signaling issues. The card is 100% software configurable.

Finally, a BRI card that upholds Sangoma's high standards of quality in engineering and untiring product support.

Architecture

The A500 consists of a Remora[®]; BRI daughterboard mounted on the AFT PCI card. The Remora[®]; BRI card has three sockets, each of which can accept an S/T BRI module. One S/T BRI module has two S/T four wire interfaces, which support TE or NT modes of operation. Changing modes requires no jumpers - simply invert the module.

Up to three additional Remora[®]; daughterboards can be mounted in empty slot positions beside the A500 assembly. These are connected to the A500 by a special backplane bus connector.

Technical Specifications

- From 2 to 24 ports are supported. Mix TE and NT modes, as required. Changing modes requires no jumpers - simply invert the colour-coded module.
- Supports Asterisk[®]; Yate[®]; FreeSwitch[®]; CallWeaver[®]; PBX/IVR projects, as well as other Open Source and proprietary PBX, Switch, IVR or VoIP gateway applications.
- Single synchronous PCI and PCI Express interface for all 24 BRI interfaces.
- Six ports per Remora[™] card.
- Dimensions: 2U Form factor: 187mm x 55mm for use in restricted chassis.
- Short 2U compatible mounting clips included for installation in 2U rackmount servers and high quality, tested 2m 8-pin RJ45 port splitter cables included.
- 32 bit bus master DMA data exchanges across PCI interface at 132 Mbytes/sec for minimum host processor intervention.
- Autosense compatibility with 5 V and 3.3 V PCI busses.
- Fully PCI 2.2 and PCI Express compliant, compatible with all commercially available motherboards, proper sharing of PCI interrupts.
- Intelligent hardware: Downloadable FPGA programming with multiple operating modes. Add new features related to voice and/or data when they become available.
- Power: 800mA peak, operational 300mA max at +3.3 V or 5 V.
- Temperature range: 0 - 50[°]C.
- Optimized DMA stream and hardware-level HDLC handling unload the host CPU.
- Raw bitstream interfaces can be used to support arbitrary non-standard line protocols, such as non-byte aligned monosynch or bisynch.
- WANPIPE[®]; supports certified, field tested, and reliable Frame Relay, PPP, HDLC and X.25.

Price: £57.09
