

Sangoma Vega 200 Dual E1/ T1 Digital Gateway VS0155



Product Name: Sangoma Vega 200 Dual E1/ T1 Digital Gateway VS0155

Manufacturer: Sangoma

Model Number: VS0155

Sangoma Vega 200 Dual E1/ T1 Digital Gateway VS0155

The Sangoma Vega 200 VoIP gateway connects digital telephony equipment to IP networks. Each unit purchased comes ready to use with capacity for 60 simultaneous calls. There are no future options or upgrades available. Each E1/T1 interface can be independently configured as network side or terminal side. The Vega 200 gateway can therefore be connected to a PBX & the PSTN simultaneously. This configuration provides:

- No disruption to the configuration of existing equipment
- Flexibility & choice for call routing

Integrated Bypass Relays For Resiliency The Sangoma Vega 200 gateway incorporates additional RJ45 sockets and fails over to these during outages. This resource can be utilised to achieve hardwired connection from the PBX to the PSTN for instances when the Vega is installed between the two. Or alternatively to failover to a back-up E1/T1 Vega gateway & thereby providing dual redundancy. The Vega 200 gateway supports the following signalling schemes:

- ETSI ISDN
- NI1, NI2, AT&T 5ESS, DMS100
- ISO QSIG Basic Call & QSIG feature transparency
- Channel Associated Signalling (CAS)

The Vega 200 gateway has proven interoperability with a wide range of existing telecommunications & VoIP equipment.

Sangoma Vega 200 Dual E1/ T1 Digital Gateway VS0155 Technical Specifications:

VoIP Interface

- SIP
- H.323 version 4
- Audio codecs:
 - G.711 (a-law/µ-law) (64 kbps)
 - G.729a (8 kbps)
 - G.723.1 (5.3/6.4 kbps)
 - Clearmode
- FAX Support – up to G3 FAX, using T.38
- Modem Support – up to V.90, using G.711
- Up to 60 VoIP channels

Telephony Interfaces

Primary Rate ISDN (User configurable NT/TE):

E1

- Euro-&ISDN
- ISO QSIG
- VN4
- QSIG Feature Transparency (H.323)
- CAS R2MFC

Sangoma Vega 200 Dual E1/ T1 Digital Gateway VS0155

T1

- NI1/NI2
 - AT&T 5ESS
 - DMS100
 - CAS (RBS)
 - E&M wink start
 - Loop start
 - Ground start
-
- ISO QSIG
 - QSIG Feature Transparency (H.323)
-
- Bypass relays terminating onto RJ45 for resiliency

LAN Interfaces

- 2 RJ-45s, 10 BaseT/100 BaseTX, full/half duplex

Identification

- Caller ID presentation
- Caller ID screening allows connections to be accepted only from selected call sources
- SIP Registration & Digest Authentication
- H.323 gatekeeper registration

Operations, Maintenance & Billing

- HTTP(S) web server
 - RADIUS Accounting & Login
 - Remote firmware upgrade:
 - Auto code upgrade
 - Auto configuration upgrade
-
- SNMP V1, V2 & V3
 - TFTP/FTP support
 - VT100 – RS232/Telnet/SSH

Routing & Numbering

- Dial Planner – sophisticated call routing capabilities, standalone or gatekeeper/proxy integration
- Direct Dialing In (DDI)
- SIP registration to multiple proxies
- NAT traversal

Security & Encryption

- Management – HTTPS, SSH Telnet

Sangoma Vega 200 Dual E1/ T1 Digital Gateway VS0155

- Configurable user login passwords

Call Quality

- Adaptive jitter removal
- Comfort noise generation
- Silence suppression
- 802.1p/Q VLAN tagging
- Differentiated Services (DiffServ)
- Type of Service (ToS)
- QoS statistics reporting
- Echo cancellation (G.168 up to 128ms)

Certification EMC (ClassB)

- EN55022
- EN55024
- FCC Part 15
- AS/NZS3548
- VCCI

Safety

- EN60950
- IEC60950
- UL60950
- AS/NZS60950

Telecoms (ISDN)

- E1: TBR4
- T1: FCC Part 68
- T1: CS-03

Environmental

- 0° .. 40°C
- 0% .. 90% humidity (non-condensing)

Indicators

LED:

- Power
- ISDN: NT/TE & Link up
- LAN: Speed, Activity

Physical Dimensions

- 437mm (17.2") x 43mm (1.7") x 275mm (10.8") width/height/depth
- Weight: 6.5kgs
- Rackmount: brackets supplied 483mm (19") 1U

Power

- 100..240 VAC, 47..63 Hz, 1..0.5 A

Sangoma Vega 200 Dual E1/ T1 Digital Gateway VS0155

- -48V DC also available, 1.2A (Max)

Program Storage

- Code & configuration data are stored in FLASH & executed from RAM.

Price: £1,394.00

VoIPVN <http://voip.com.vn>