

Snom MeetingPoint Conference Phone



Product Name: Snom MeetingPoint Conference Phone

Manufacturer: Snom

Model Number: MEETINGPOINT

snom MeetingPoint Conference Phone

The snom MeetingPoint Conference Phone is the perfect solution for anybody who makes frequent cross-location consultations. The snom MeetingPoint is the only SIP conference phone that allows you to use Microsoft Office Communication Server 2007 R2 and Standard SIP accounts in one conference phone in parallel. It is already compatible to Microsoft Office Communications Server 2007 R2 with the snom OCS edition in parallel use to any SIP based IP pbx.



With the new snom MeetingPoint you are able to allow for a total of external four parties to participate at the phone conference from different locations all over the world. This helps to control the time- and travel budget of every company!



The snom MeetingPoint is perfectly qualified for use in middle to large conference rooms. As result of the reliable suppression of disturbing background noise and its excellent sound quality you can hold your telephone conferences in large groups of up to 10 persons without affecting the intelligibility of the call. Three speakers, equipped with full duplex broadband audio (7 kHz, codec “G.722”) provide balanced and full sound, which snom customers also know from the snom klarVoice handset. The integrated special microphones ensure that your interlocutors feel as if you are sitting in the neighboring office - and not on the other side of the world!

Snom MeetingPoint Conference Phone



Additionally the snom MeetingPoint has all the advantages from a snom VoIP phone: highest security combined with several features like the snom Flexor CTI or the snom OCS edition. 12 different SIP identities give you the flexibility you need.



Additionally, the new snom 820 WiFi enables you to install the phone in any surrounding you are. Whatever you prefer, the snom 820 is prepared for any option: Power over plug, Power over Ethernet (PoE) or WiFi.

Snom MeetingPoint Conference Phone

- Omnisound Full duplex wideband sound technology
- Management of up to 4 external participants
- Recording range up to 30M or 10 participants
- Simultaneous management of internal and external telephone listings (LDAP)
- Connection type for add-on microphones for a larger reception range
- Microsoft Office Communication Server 2007 R2 ready
- Multiple SIP registrations
- OpenVPN

General Features

- Size: Diameter: 240mm, Height: 77mm
- Display: Background-lit graphical LCD, 128x64 pixels
- Weight: 1kg
- Color: black
- Keypad: Alphaneumeric 0-9, *, #, dial, hang up, mute, increase volume, menu, conference, recording, volume control, 5 keys for navigation in the menu system
- Microphone: Circular (360) recording characteristics
- Reception range: up to 30m2, <10 persons
- Speaker: Frequency range: 150-15000 Hz playback
- Volume: 90db SPL 0.5m. Equalizer function
- Anti-theft protection: Kensington security slot

Connections

- Network connection: 1x RJ-45, PoE 10/100MBit
- Power Supply: Power adapter 100-240 VAC/14 V DC - PoE
- Add-on microphones: modular 4/4 possible

Surrounding Conditions

- Temperature: 5°-40°C.
- Air Humidity: 20 - 80%
- Suggested acoustic room conditions
- Reverberation time: 0.5 S Rt 60
- Background noise: 45 dbA

Permissions

- Telecoms: TBR21, 47 CFR part 68/ TIA, IC CS-03 Issue 1999/01/01
- EMC: EN301 489-1,3. EN 300 220-1,2, FC subpart B and C.
- Electrical safety class: UL 60950-1, EN 60950-1:200

Price: £478.72
