

Product Name: Snom UC600 Lync IP Phone Manufacturer: Snom Model Number: SNOMUC600

Snom UC600 Lync IP Phone

The snom UC600 is an IP desk phone with comprehensive features and function sets so a wide range of business communications challenges can be overcome. The snom UC600 Lync IP Phone has many features including a 2-line backlit LCD screen, a presence status light for effectively directing calls and a series of convenient keys. Snom UC600 Key features

- Two-line backlit LCD display
- Redial key, Hash key, delete key
- Volume control
- Microphone mute key
- Headset key
- Speakerphone key
- Easy to use
- Facilitates call handling from phone to PC
- Includes standard keys to control incoming calls, volume or speakerphone
- Excellent voice quality
- Improved presence indication

The UC600's functions are vital for everyday working life. As a traditional VoIP desk phone, the snom UC600 is designed and qualified for use with Microsoft Lync. Snom UC600 Technical Specification General Features

• Size: Handset: 19.05 x 5.08 x 1.91 cm (7.5 x 2.0 x 0.75 in) Cradle: 8.89 x 13.97 x 12.7 cm (3.5 x

- 5.5 x 5.0 in)
- Weight: 1.06 kg
- Safety: IEC 60950-1:2005
- Certifications: FCC Class B, CE Mark, CSA Mark
- Power consumption: Via the USB connection to the PC (USB 2.0, < 500mA 5 V)

Device Controls and Keypad

- 4x3 Dialpad
- Redial key
- Flash Key
- Delete Key
- Mute/un-mute key
- Speaker on/off key
- Handset/headset key
- Volume up/down key
- LED Indicators
- Off hook indicator
- Voice messaging indicator
- Speakerphone indicator
- Headset indicator
- Call forwarding indicator
- Multi-color LED presence indicator

Audio

Snom UC600 Lync IP Phone

- TIA-920
- Frequency response: 200 7kHz
- >58dB [200, 7000] Hz
- Dynamic range: >80 dB (@ 1kHz)
- Total Harmonic Distortion + Noise: <3% (@ 200 7kHZ)
- Auxiliary Audio Output
- RJ-22 headset jack with built-in amplifier

Audio Enhancements

- Automatic Gain Control
- Dynamic Noise Reduction
- Acoustic Echo Cancellation

Minimum System Requirements

- Microsoft Windows XP or Windows Vista
- PC with Office Communicator 2007 R2 version 3.5.6907.37 or a later version installed
- One available USB 2.0 compliant connection

Environmental Requirements

- Temperature: 0°C to 40°C (32°F to 104°F)
- Relative Humidity: 95% max (non- condensing)
- Altitude: -304.8 meter to 3962.4 meter (-1000 feet to 13,000 feet)
- Light Exposure: Fluorescent overhead lighting and window filtered daylight (typical offices)

TSAnet

• Device makers and MS participate in common support infrastructure (TSAnet) for rapid resolution of support tickets

Snom UC600 ships with:

- Snom UC600 base
- Handset
- 1.8 m (6 ft.) handset curly cord
- Captive USB cable
- Quickstart Guide

User Interface

- Redialing last number dialed
- Holding/ unholding call
- When dialing: Deleting entire number
- Delete last digit entered on keypad
- Reject incoming call
- Turning speakerphone on and off
- · Selecting the headset as the audio device
- Muting/ unmuting microphone
- Adjusting volume

Price: £91.62

Snom UC600 Lync IP Phone

SPAN KILO