

Product Name: SpectraLink 8440 Wireless IP Phone in Blue

Manufacturer: Spectralink

Model Number: 2200-37178-101

SpectraLink 8440 Wireless IP Phone in Blue

The Polycom SpectraLink 8400 VoWLAN series handsets deliver on a fundamental need for enterprise-grade on-site voice mobility. Characterized by market-leading Polycom HD Voice™ quality, durability, and broad telephony and WLAN interoperability, SpectraLink 8400 handsets deliver a reliable user experience and predictable return on investment. Please see the information below if you are not sure what size system or type of technology suits your needs most:

- When to choose a Polycom KIRK solution or a Polycom Wi-Fi solution
- The benefits of a choosing a Polycom mobility solution
- Polycom KIRK & amp; SpectraLink business grade on-site mobility solutions

The SpectraLink 8400 series enhances the customer value proposition through an optional integrated barcode scanner and an enhanced standards-based applications interface. In partnership with the Polycom applications development ecosystem, the SpectraLink 8400 product toolset enables new opportunities for end-user productivity solutions. Product Presentation

Spectralink REACH: Improve Nurse Response Times

Spectralink SAFE: Protection and Peace of Mind for Nurses

Spectralink Mobile Workforce Solutions: Solving Every Day

Polycom SpectraLink 8440 Technical Specifications Display:

- 2.2-inch 240 x 320 resolution
- 65,000 color palette

Buttons:

- Four (4) context-sensitive softkey buttons
- Dedicated Push-to-Talk
- Five-way navigation and select control
- Home & amp; back navigation keys
- Up/Down volume control
- Barcode reader (8450 handset)
- Start and End Keys

Status LED

- · Message (voicemail) waiting
- Out of coverage
- Phone ringing

Peripheral Interfaces

- Micro USB interface for wall charging and configuration
- 2.5mm TRS connector for wired headset
- Bluetooth

Batteries

- Two easy-access cosmetic battery capacity options
- Standard Up to 8 hrs talk time, 80hrs standby time
- Enhanced Up to 12 hrs talk time, 120hrs standby time

Durability

- Drop/shock: MIL STD 810F, method 516.5 procedure VI
- Ingress protection standard IP-64 per IEC 60529
- Rubberized molding
- Magnesium LCD mounting

Environmental

- Operational temperature: 32F to 104F (0 to 40C)
- Storage temperature: -22 to 140F (-30 to 60C)

Dimensions and Weight

- Dimensions: 147mm x 53mm x 28mm
- Weight: 6.2 oz

Wi-Fi 802.11a

- 5.15 5.25 GHz
- 5.25 5.35 GHz
- 5.47 5.725 GHz
- 5.725 5.825 GHz
- 6, 9, 12, 18, 24, 36, 48, 54 Mbps

802.11b

- 2.4 2.4835 GHz
- 1, 2, 5.5, 11 Mbps

802.11g

- 2.4 2.4835 GHz
- 6, 9, 12, 18, 24, 36, 48, 54 Mbps

- 2.4 & 5 GHz
- 21.7, 43.3, 65, 72.2 Mbps

2.4GHz and 5GHz dynamic band roaming supported *Single-stream, 20MHz channel with SG Bluetooth

- Version 2.1, HSP Version 1.2
- Class 1 support with range of ~10 meters

Telephony Features
Rich call server feature integration and native Push-to-Talk
Call Handling Features*

- Up to 6 telephone line appearances
- Call Hold/Resume function
- Last Call Return
- Music on Hold
- Consultation Hold
- Call Transfer (Attended, Unattended)
- Overlap dialing
- Bridged Line Appearance (BLA)
- Three-Way Conferencing (local)
- Find-Me call forking
- Call Screening (Incoming, outgoing)
- Automatic Answer
- Call Park & Damp; Retrieve
- Group Call Pickup
- Call Waiting
- Multiple Calls per Line
- Do Not Disturb
- · Calling party ID (name and number)
- Called party ID (name and number)
- Connected party ID (name and number)
- Call Forward (Busy, No answer, Unconditional)
- Call Reject

*Summary only – actual feature support will vary among call platforms Codecs

G.711 (a-law, u-law), G.729, G.722, G.722.1

Push-to-Talk (PTT)/Paging

- On-board native ' walkie-talkie' capability
- One-to-one, one-to-many broadcast communication
- 24 configurable channels
- Priority, default channel

Additional Telephony Features

- RTCP (RFC3550, 1889)
- Call server redundancy
- Predictive dialing from contacts list
- Recent call lists

Ease of Provisioning, Performance and Fault Management Provisioning

- Server based central provisioning via FTP, TFTP, HTTP or HTTPs
- Centralized user administration
- Provisioning and call server redundancy
- Initial configuration via USB
- Unicode UTF-8 Multilingual User Interface

Performance and Fault Management

- On-board site survey and diagnostics tools
- Enhanced syslog reporting
- Roaming and handoff reporting
- Event logging
- Hardware diagnostics
- Status and status reporting
- PING support (initiate and response)
- Traceroute

Configuration Management

- User and administrator login and privileges
- PC-connected (USB) and remote over-the-air configuration management

Applications Tools

Feature rich data applications interface options Polycom XML Applications Program Interface

- Standards-based XHTML API
- On-board WebKit-based browser (JavaScript, CSS, DOM) for rich applications integration
- Bundled with Polycom Productivity Suite for Corporate Directory access using LDAP and Voice Quality Monitoring

Polycom Open Application Interface (OAI)
Backward compatibility with SpectraLink OAI applications
Instant Messaging

- Handset-to-handset, PC client-to-handset IM support via
- Microsoft OCS 2007 R2 Instant Messaging

Real Time Location Services (RTLS)
Embedded RTLS beacon (Ekahau) for location tracking
Calendar - Exchange Server Integration

- Day and month view
- Meeting reminders

Performance Industry leading voice and call quality Audio quality

- TIA 810B, TIA 920 audio quality standards
- Full-duplex audio (compliant with IEEE 1329 full duplex standards)
- Voice activity detection (VAD)

- Comfort noise fill
- Adaptive jitter buffer & packet loss concealment
- Acoustic echo cancellation & amp; background noise suppression

Quality of Service (QoS)

- WMM (Wi-Fi Multimedia)
- WMM-Power Save, WMM-Admission Control (draft)
- IEEE 802.1p/Q tagging (VLAN)/DSCP tagging

Security

- WEP, WPA-Personal, WPA2-Personal, WPA2-Enterprise with
- 802.1X (EAP-FAST, PEAP-MSCHAPv2) with Opportunistic
- Key Caching (OKC) and Cisco Client Key Management
- (CCKM)
- Media encryption via Secure Real-Time Protocol (SRTP)
- SIP signaling encryption via Transport Layer Security (TLS)
- Server-based configuration file encryption (AES 128bit)
- HTTPS secure provisioning
- Support for signed software executables

Networking

- Strong support for Networking Standards
- Address assignment via Manual or Dynamic host configuration protocol (DHCP)
- Domain name resolution via Domain Name Service (DNS)
- Time and date synchronization using Simple Network Time Protocol (SNTP)
- Lightweight Directory Access Protocol (LDAP) for directory lookup and download
- IEEE 802.1p/Q tagging (VLAN)/DSCP tagging

Data Capture Specifications

- · High-performance scanning
- 1D CMOS Linear Imager

Features

- Light Source 617 nm Highly Visible LED
- Scan Rate Up to 500 scans/s
- Scan Angle 38°
- Label print contrast Down to 25%
- Min. label x. dimension 0.15mm (6 mils)
- Reading distance Up to 40cm (16in.)

Barcode Symbologies

- RSS, Stacked RSS, RSS-14, GS1-DataBar, Code 39, Code 93, Code 128, UPC (E&A)
- Note: 2D area imager solution available at a later date

Usability

Intuitive and user-friendly

User Profiles

Downloadable to any handset with ID and Logi

Additional

- Intuitive Graphical User Interface
- Selectable wallpaper/background
- Adjustable display brightness
- Backlit keypad with adjustable timeout period
- Ten (10) selectable ring tones
- Ten (10) selectable alert tones
- Multiple vibrate cadence options
- Vibrate-to-ring options
- Audible and vibrate notification options
- Speed dial menu list
- Contacts directory with support for 1000 local entries
- Call logs Minimum of 20 logged entries for each call type (Incoming, dialed, and missed)
- Emergency system-wide speed dial
- Auto-answer & amp; any key answer capability
- Selectable ring tones

Price: £429.60